



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



LOW VOLTAGE

SFE Fast-Acting Type



ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Opening Time
110%	4 hours, Minimum
135%	1 hour, Maximum
200%	10 seconds, Maximum

APPROVALS: Listed by Underwriters Laboratories.


DESIGN STANDARDS: U.L. Standard 275. SAE (Society of Automotive Engineers) J554.

ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating	Fuse Length
307 004	4	32	5/8"
307 006	6	32	3/4"
307 07.5	7½	32	7/8"
307 009	9	32	7/8"
307 014	14	32	1 1/16"
307 020	20	32	1 1/4"
307 030	30	32	1 3/16"



3AG Fast-Acting Type



ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Ampere Rating	Opening Time
100%	4-35	4 hours, Minimum
135%	4-35	1 hour, Maximum
200%	4-30	10 seconds, Maximum
200%	35	20 seconds, Maximum

APPROVALS: Listed by Underwriters Laboratories and Certified by CSA through 30 amperes.

DESIGN STANDARDS: U.L. Standard 275.

ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating
311 004	4	32
311 005	5	32
311 006	6	32
311 007	7	32
311 07.5	7½	32
311 008	8	32
311 010	10	32
311 012	12	32
311 015	15	32
311 025	25	32
311 030	30	32
311 035	35	32

For 20-ampere rating use 307 020.

