

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









This document was generated on 03/21/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 14-44-1204

Status: Active

Overview: C-Grid® Products

Description: 2.54mm Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row,

Version D, Back Ribs, for Wire Size 24 AWG, 0.38µm Gold (Au), 4 Circuits

Documents:

3D Model Product Specification PS-70400 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family Ribbon Cable / Wire Trap Connectors

Series <u>70475</u>

Comments Terminals Preloaded

Component Type Housing Glow-Wire Compliant No

Overview <u>C-Grid® Products</u>

Product Name SLTM

UPC 800753605701

Physical

Circuits (Loaded) 4
Circuits (maximum) 4
Color - Resin Black
Durability (mating cycles max) 50
Entry Angle Vertical
Flammability 94V-0
Lock to Mating Part None

Material - Metal Phosphor Bronze

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin Polyester Alloy

Number of Rows 1
PCB Retention None
Packaging Type Tube
Pitch - Mating Interface 2.54mm
Polarized to Mating Part No
Stackable Yes
Surface Mount Compatible (SMC) N/A

Temperature Range - Operating -40°C to +105°C Termination Interface: Style IDT or Pierce Wire Insulation Diameter 1.35mm max.

Wire Size AWG 24

Wire/Cable Type Discrete Wire, Ribbon Cable


Electrical

Current - Maximum per Contact 3A Voltage - Maximum 250V

Material Info

Old Part Number A-70475-0598

Reference - Drawing Numbers



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed

Not Reviewed

Low-Halogen Status

Not Reviewed



Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

70475 Series

Mates With

70004 Interim Clip (Single Row), 70013 Interim Clip (Dual Row)

Use With

7307 Tinned 28AWG, 7767 Topcoat 28AWG, 24241 Tinned 26AWG, 8996 Topcoat 26AWG, 24226 Tinned 24AWG, 8997 Topcoat 24AWG, 24369 High Flex 26AWG, 24389 High Flex 24AWG

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product #

Ribbon Cable Tool 0622016600 Kit, Press Not Included

This document was generated on 03/21/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION