

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Direct Mount Terminals Feed Through		MK 5/2	KS 210		SLS 2/2 SLS 2/4		
		e e		9 9			
		0 9 0 0			00	0	
Available Options	Version	Type Part No.	KS 4 with D 4  Type	Part No.	Туре	Part No.	
Available Options	2 pole	MK 5/2 KrG <b>0243820000</b>	KS 2 KrG	0134420000		0213420000	
	3 pole		ICC 4 IC+C	04.40000000	CI C 0/4 K*C	0040400000	
	4 pole Slotted 4 pole		KS 4 KrG	0140320000		0240420000 0480320000	
	6 pole		KS 6 KrG	0140620000			
	10 pole		KS 10 KrG	0141620000			
	12 pole cover	D 2 (for MK 5/2) <b>0244060000</b>	D 2 (for KS 2)	0134500000			
	cover	B 2 (101 1111 (1012)	D 4 (for KS 4)	0140500000			
	cover		D 6 ( for KS 6)	0140800000			
Dimensions	cover		D 10 (for KS 10)	0141800000			
Width / Length / Height	mm (in.)	40/18/15.5 (1.57/.71/.61)	See table below		See table bel	OW	
		-	- ()		- /		
Insulation stripping length  Technical Data	mm (in.)	5 (.20)	8 (.32)		8 (.32)		
Rated voltage / rated current / wire size	UL						
CSA		300 V / 25 A / #20 14 AWG			300 V / 10 A / #22 10 AWG		
	VDE	500 V / 25 A / 2.5 mm <sup>2</sup>	500 V / 36 A / 44	1 mm²	380 VAC / 16	S A / 4 mm²	
Torque	Nm (in. lb.) 0.4 (3.5) 0.5 (4.5)		0.5 (4.5)		1.2 (10.4)		
Clamping screw	M	2.5	3		3.5		
		Cover	Marking tag cover		#1° #		
		\					
		M 2.5x6	Ø 4.2	M3x8	4.2	+ 22.5 +	
		15.5 B D D		000	-101-	→ 28.5 →	
		04.2		b		+	
					<del>00000</del>	200	
					4.2	22.5	
			Dimensions				
			Type	a b			
			KS 2	42 32			
			KS 4 KS 6	66 56 90 80			
				138 128			
Tag Block / Plastic Rivet / Insulating Sleeve			Туре	Part No.	Туре	Part No.	
					IH 2.8	0386060000	+
					IH 6.3	0386260000	
Marking Strips	Print Printed		ELSb 2	0143200000			
	riiited		ELSb 4	0143200000	BSTb 12/4	0248400000	
			ELSb 6	0143400000			
	ا- مغماسموا ا		ELSb 10 ELSo 2	0143500000 0142800000			_
	Unprinted		ELSo 2	0142800000			-
			ELSo 6	0143000000	BSTo 12/4	0248300000	
			ELSo 10	0143100000			