



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





General ordering data

Order No.	0185220000
Part designation	SAKG 40 II/GW
Version	Special terminal, special connections, 95 mm ² , Screw connection, KrG, Medium yellow, TS 32
EAN	4008190088408
Qty.	10 pc(s).

Product notes

Note, technical data	Conductor connection with cable lugs according to DIN 46234, from 10 .. 95 mm ²
----------------------	--

Additional technical data

Colour of insulating material	Medium yellow
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 32
Insulating material	KrG
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	Open
Operating temperature range	- 60 °C, + 130 °C
Product family	SAK Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	5VA
Version	Stud terminal

CSA rating data

Voltage (CSA)	600 V
CSA current	250 A
Min. cross-section (CSA)	AWG 2/0
Max. cross-section (CSA)	AWG 4/0

Conductors for clamping (rated connection)

Clamping range, min.	10 mm ²
Clamping range, max.	95 mm ²
Type of connection	Screw connection

Conductors for clamping (rated connection)

2nd type of connection	screwed
Connection direction	on side
No. of connections	1
Clamping screw	M 10
Tightening torque range	10...20 Nm
Solid, max.	16 mm ²
AWG conductor size, min.	AWG 2/0
AWG conductor size, max.	AWG 4/0
AWG conductor size, min.	67.44 mm ²
AWG conductor size, max.	107.22 mm ²

Dimensions

Width	46 mm
Height of lowest version	53 mm
Length	90 mm
Weight	217.9 g
TS 32 offset	45 mm

Rating data

Rated cross-section	95 mm ²
Rated voltage	1,000 V
Rated impulse voltage	8 kV
Rated current	232 A
Standards	IEC 60947-7-1
Current with max. conductor	232 A
Pollution severity	3

UL rating data

Voltage (UL)	600 V
Current (UL)	230 A
Min. cross-section (UL)	AWG 1
Max. cross-section (UL)	AWG 4/0

Approvals

Approvals institutes



Downloads

DXF	01428_SAKG_40_II-GW_DXF.dxf
STEP	0185220000_01428_SAKG_40_II-GW_STP.stp

Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-31

Classifications

eClass 5.0	27-14-11-31
eClass 5.1	27-14-11-31

Similar products

Order No.	Part designation	Version
0286820000	SAKG 40 I	Special terminal, special connections, 95 mm ² , Screw connection, KrG, Medium yellow, TS 32
0170520000	SAKG 40 II	Special terminal, special connections, 95 mm ² , Screw connection, KrG, Medium yellow, TS 32
0286920000	SAKG 40 III	Special terminal, special connections, 95 mm ² , Screw connection, KrG, Medium yellow, TS 32