## mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



NOTES: MAT'L: COPPER	COPPER						INE NO.	40. AA- CD -203-01	
PLATING : ELECTRO-TIN (.0003 MIN.) (2) INSULATION : MOLDED PVC (RED)	ELECTA DN:MOL	DED PV	.0003 M	MIN.)	· <b>–</b>	LOI			
STUD SIZES:(-,005)	:(;005	~			145				
02 = 094					3.68 MWIU				
N 1	•				•—		405 MAX		
			•	*				-	
N IF			ISTING	UL LISTING E32244 CSA LISTING 18689			Σ	MWID = MAXIMUM WIRE INSULATION DIAMETER	- a
38 - 39U	ALL DI	ALL DIMENSIONS= INCHES	4S= INCHE	HES			-	WIRE SIZE: 22 - 18 AWG	
PART NUMBER	* W * 1.010	°C″ MIN.	<sup>»</sup> د" ۸۸۲.	NIN			AVAILABLE STUD SIZES	STOCK THICKNESS	
AA-234-	291	<u>-207</u> 5.26	. <u>785</u> 19.94	062			04x ¦06x,08x	.026 - 384 .71	
AA-238 -	.245 6.23	. <u>207</u> 5.26	. <u>785</u> 19.94	.062 1.57			04X,06X	.02 <del>8</del> -88 0	
AA - 291 -	.420	.235 5.97	.865 2197	054			06x,08x,10x	.03 <sup>†</sup> .00	· · · · · · · · · · · · · · · · · · ·
AA - 294 -	. <u>375</u> 9.53	.235 5.97	. <u>868</u> 2205	.054 1.37			06x,08x,10x	100. <sup>±</sup> 100. .79	
AA - 297	.325 <u>8.26</u>	<u>.235</u> 5.97	. 865 21.97	.054	·		04X,06X,08X	. <u>031<sup>±.001</sup></u> .79	•
DIMENSIONAL TOLERANCES	ERANCES	REFERENCE		۲Z				F C molex	
			DRWN, BY	_	+A.2	e i	TEDMINAL	INCOARDAALO	
+1	5		AND	N IN	0.0.1		INSUL KRIMP		
							200 SERIES	NO. A USIOMER	