



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



NTC Thermistors, Radial Leaded and Coated



FEATURES

- Small size - conformally coated
- Wide resistance range
- Available in 7 different R-T curves
- Available in point matched tolerances down to 1 % and curve tracking precision down to ± 0.2 °C
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT

| QUICK REFERENCE DATA | | |
|--|---------------------------|----------|
| PARAMETER | VALUE | UNIT |
| Resistance value at 25 °C | 30 to 1M | Ω |
| Tolerance on R_{25} -value (point matched) | $\pm 1, \pm 5, \pm 10$ | % |
| Temperature accuracy (curve tracking) | $\pm 0.2, \pm 0.5, \pm 1$ | °C |
| $B_{25/75}$ -value | 3477 to 4842 | K |
| $B_{25/85}$ -value | 3468 to 4875 | K |
| Maximum dissipation | 50 to 100 | mW |
| Dissipation factor δ (for information only) | 2 to 3.5 | mW/K |
| Thermal time constant τ (for information only) | 6 to 14 | s |
| Response time (oil) (for information only) | 1.3 | s |
| Operating temperature range at zero power (short term) | -40 to +125 (150) | °C |
| Weight | ≈ 0.075 to 0.15 | g |

APPLICATIONS

Temperature measurement, sensing and control in industrial, consumer and telecom applications. For on-board sensing or for accurate remote sensing in metal probes or housings.

DESCRIPTION

Models T, M, and C are conformally coated, leaded thermistors. The coating is baked-on phenolic for durability and long-term stability. Models M and C have tinned solid copper leads. Model T has solid nickel wires with Teflon® insulation.

DESIGN-IN SUPPORT

For complete Curve Computation, visit:
www.vishay.com/thermistors/curve-computation-list/

| T, M, C PRODUCT DATA AND R_{25} RESISTANCE RANGE AVAILABILITY | | | | | | | |
|---|-----------------|-----------------|------------------|-----------------|-----------------|-----------------|--------------------------------|
| CURVE | $B_{25/75}$ (K) | $B_{25/85}$ (K) | TCR_{25} (%/K) | T (k Ω) | M (k Ω) | C (k Ω) | $R_{25} \pm$ TOL. AVAILABILITY |
| 2 | 3477 | 3486 | -3.84 | 0.03 to 3.3 | | | 1, 5, 10 |
| 9 | 3679 | 3694 | -4.03 | 10 to 56 | | | 1, 5, 10 |
| 8 | 3925 | 3943 | -4.30 | 20 to 220 | | | 1, 5, 10 |
| 1 | 3964 | 3974 | -4.39 | 0.2 to 18 | | | 1, 5, 10 |
| 4 | 4247 | 4262 | -4.67 | 10 to 100 | | | 1, 5, 10 |
| 7 | 4437 | 4461 | -4.83 | 10 to 270 | | | 1, 5, 10 |
| 12 | 4842 | 4875 | -5.23 | 47 to 1000 | | | 1, 5, 10 |
| Maximum dissipation at 25 °C in mW | | | | 50 | 75 | 100 | |
| Dissipation factor in mW/K ⁽¹⁾ | | | | 2.0 | 2.5 | 3.0 | |
| Response time in s ⁽¹⁾ | | | | 1.3 | 1.2 | 1.4 | |
| Thermal time constant in s ⁽¹⁾ | | | | 14 | 10 | 6 | |

Note

⁽¹⁾ For information only, dissipation factor, response time, and thermal time constant are wire type and product size dependent.

| STANDARD RESISTANCE VALUES at 25 °C in Ω | | | | | | | | | |
|---|-----|-----|------|------|------|-----|------|------|------|
| 33 | 82 | 270 | 680 | 2.2K | 5.6K | 18K | 50K | 150K | 500K |
| 39 | 100 | 330 | 820 | 2.7K | 6.8K | 22K | 56K | 220K | 560K |
| 47 | 120 | 390 | 1K | 3.3K | 8.2K | 27K | 68K | 270K | 680K |
| 50 | 150 | 470 | 1.2K | 3.9K | 10K | 33K | 82K | 330K | 820K |
| 56 | 180 | 500 | 1.5K | 4.7K | 12K | 39K | 100K | 390K | 1M |
| 68 | 220 | 560 | 1.8K | 5.0K | 15K | 47K | 120K | 470K | |

Note

- Most popular and available values, intermediate resistance values and tolerances available on request.


| GLOBAL PART NUMBER AND ORDERING INFORMATION | | | | | | | | | | | | | |
|---|---|--------------|---|--------------------------|---|--------------------------------------|---|--|---|--|--|--|--|
| Global Part Numbering: 01C2001FP for POINT MATCHED THERMISTORS | | | | | | | | | | | | | |
| 0 | 1 | C | 2 | 0 | 0 | 1 | F | P | | | | | |
| CURVE NR | | GLOBAL MODEL | | RESISTANCE VAL | | POINT MATCH TOLERANCE | | PACKAGING | | | | | |
| 01 02 04 07 08 09 12 | | T M C | | 2001 = 2K 1503 = 150K | | F = ± 1 % J = ± 5 % K = ± 10 % | | F = lead (Pb)-free, bulk P = tin / lead, bulk | | | | | |
| Global Part Numbering: 01C2001SPC3 for CURVE TRACKING THERMISTORS | | | | | | | | | | | | | |
| 0 | 1 | C | 2 | 0 | 0 | 1 | S | P | C | 3 | | | |
| CURVE | | GLOBAL MODEL | | RESISTANCE VAL | | CHARACTERISTICS | | PACKAGING | | CURVE TRACK TOLERANCE ⁽¹⁾ | | | |
| 01 04 08 09 | | T M C | | 2001 = 2K | | S | | F = lead (Pb)-free, bulk P = tin / lead, bulk | | A3 A4 A5 A8 B3 B4 B5 B8 C3 C5 C8 | | | |

Note


(1) See following pages for tolerance explanations and details.

DIMENSIONS in inches (millimeters)

TYPE M, C



TYPE T



| PRODUCT TYPE | WIRE GAUGE/DIAMETER ⁽¹⁾ |
|--------------|------------------------------------|
| Type M | AWG 30: 0.0100 (0.254) |
| Type C | AWG 28: 0.0126 (0.320) |
| Type T | Insulated AWG 30: 0.0100 (0.254) |

Note

(1) Additional wire gauges (non-insulated) available as AWG24 (type E), AWG26 (type B) and AWG32 (type F). Please contact [vishay \(thermistor1@vishay.com\)](mailto:thermistor1@vishay.com) for further details.

| CURVE NUMBER | R ₂₅ MIN. (Ω) | MAX. DIAMETER (INCH (mm)) | STANDARD R ₂₅ RANGE (Ω) | MAX. DIAMETER (INCH (mm)) |
|--------------|--------------------------|---------------------------|------------------------------------|------------------------------|
| 2 | 30 | 0.342 (8.69) | 330 to 3K | 0.095 (2.41) to 0.136 (3.45) |
| 9 | 10K | 0.150 (3.81) | 10K to 56K | 0.095 (2.41) to 0.150 (3.81) |
| 8 | 20K | 0.131 (3.33) | 27K to 220K | 0.095 (2.41) to 0.125 (3.18) |
| 1 | 200 | 0.315 (8.00) | 1.8K to 18K | 0.095 (2.41) to 0.136 (3.45) |
| 4 | 10K | 0.136 (3.45) | 10K to 100K | 0.095 (2.41) to 0.136 (3.45) |
| 7 | 10K | 0.177 (4.50) | 27K to 270K | 0.095 (2.41) to 0.136 (3.45) |
| 12 | 47K | 0.252 (6.40) | 330K to 1M | 0.095 (2.41) to 0.136 (3.45) |

Note

• Maximum body diameter is dependent on selected curve number and value, the lower resistance values have the largest diameter. For a specific part number within the given resistance ranges, please contact thermistor1@vishay.com for maximum diameter information.

TOLERANCES AVAILABLE FOR TYPE T, M, AND C THERMISTORS

DESCRIPTION OF THERMISTOR TOLERANCES

The many applications of thermistors have mandated the need for two basic tolerance schemes for these products - curve tracking and point match thermistors. An example of the resistance tolerance at various temperatures for the two different tolerancing methods is described in the following graph:




Fig. 1

CURVE TRACKING TOLERANCE

Thermistors are calibrated at the high temperature of the curve track range and then final tested at the low temperature of the curve track range. This ensures that the thermistor will meet the specified temperature accuracy at every temperature within the desired temperature range. Several temperature ranges are available and the accuracy of the thermistor may be ± 0.2 °C, ± 0.5 °C, and ± 1.0 °C. The curve tracking temperature ranges and their code designators are shown in figure 1 and "Standard Electrical Specifications for Curve Tracking Thermistors" table.

To specify, add the appropriate suffix from the following table to the part number.

Example: 01M1002SFB3 = curve 1, 10 k Ω at +25 °C, curve tracking to ± 0.5 °C from 0 °C to +70 °C

| STANDARD ELECTRICAL SPECIFICATIONS FOR CURVE TRACKING THERMISTORS | | | | | | | | | | | | | |
|---|----|----------------|--------------|--------------|-----------------|--------------|--------------|-----------------|--------------|--------------|----------------|--------------|--------------|
| TEMPERATURE RANGE FOR SPECIFIED ACCURACY | | 0 °C to +70 °C | | | 0 °C to +100 °C | | | 25 °C to +90 °C | | | 0 °C to +50 °C | | |
| ACCURACY | | ± 1 °C | ± 0.5 °C | ± 0.2 °C | ± 1 °C | ± 0.5 °C | ± 0.2 °C | ± 1 °C | ± 0.5 °C | ± 0.2 °C | ± 1 °C | ± 0.5 °C | ± 0.2 °C |
| PART NO. SUFFIX | | - A3 | - B3 | - C3 | - A4 | - B4 | - C4 | - A5 | - B5 | - C5 | - A8 | - B8 | - C8 |
| CURVE NUMBER | 01 | X | X | X | X | X | n/a | X | X | X | X | X | X |
| | 04 | X | X | X | X | X | n/a | X | X | X | X | X | X |
| | 08 | X | X | X | X | X | n/a | X | X | X | X | X | X |
| | 09 | X | X | X | X | X | n/a | X | X | X | X | X | X |

POINT MATCH TOLERANCE

The standard leaded thermistors are calibrated and tested at 25 °C to a tolerance of $\pm 5\%$ or $\pm 10\%$; however, tighter tolerance, point matched thermistors are readily available as are special point match temperatures to fit your application.

Since these thermistors have only one controlled point of reference (the point match temperature), the resistance at other temperatures is given by the specific curve resistance vs. temperature ratio.

POINT MATCH TOLERANCES VS. TEMPERATURE




Fig. 1

Point match resistance tolerances at temperatures other than 25 °C are not the same as at the calibration temperature. This difference is presented in figure 2.

The tolerance at any given temperature is the point match tolerance plus a manufacturing tolerance depending on the specific curve.

DESIGN-IN SUPPORT

A spreadsheet is available for the Vishay thermistor part numbers that gives you the resistance vs temperature data, the temperature coefficients and accuracy levels at any given temperature range and step. The Steinhart & Hart formula and coefficients A, B, and C are shown as well. This data can be obtained by visiting the Vishay NTC curve computation page at: www.vishay.com/thermistors/curve-computation-list/ or send your part number with required temperature range and step to thermistor1@vishay.com.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.