



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Fuse terminals

SAKS 3 SAKS 3/35



Dimensions/approvals	
Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

13/54/61
13/54/55
12 mm/M 4/5.5 x 1

Rated data/feed through-terminal base	
Rated voltage/current/cross-section	500 V/10 A/10 mm ²
Rated impulse voltage/pollution severity	6 kV/3

400 V**/16 A/10 mm ²
6 kV/3

Further technical data	
Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4

1.2...2.4
4

Clampable conductor	
Solid H07V-U	mm ² 0.5...16
Stranded H07V-R	mm ² 1.5...10
Flexible H07V-K	mm ² 0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...10
Plug gauge according to 60 947-7-1	Size B 6
Continuous current rating of cross-connection 2...5-pole	A (QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A (QL 6...10) 36

0.5...16
1.5...10
0.5...10
0.5...10
B 6
(QL 2...5) 47
(QL 6...10) 36

SAKS 4 SAKS 4/35



24/75/73
24/75/66
14 mm/M 4/5.5 x 1

400 V**/16 A/10 mm ²
6 kV/3

1.2...2.4
4

0.5...16
1.5...10
0.5...10
0.5...10
B 6
(QL 2...5) 47
(QL 6...10) 36

SAKS 5 SAKS 5/35



28/80/80.5
28/80/66
13 mm/M 4/5.5 x 1

400 V/63 A***/16 mm ²
6 kV/3

1.2...2.4
4

1.5...16
1.5...16
1.5...16
1.5...16
B 7
(QL 2...5) 47
(QL 6...10) 36

SAKS 2 SAKS 2/35



28/80/81.5
28/80/75
12 mm/M 4/5.5 x 1

500 V/10 (25) A***/10 mm ²
6 kV/3

1.2...2.4
4

0.5...16
0.5...10
0.5...10
0.5...10
B 6
(QL 2...5) 47
(QL 6...10) 36

Rated data according to UL/CSA

Voltage/current/conductor size	UL	300 V/10 A/22...10 AWG
Voltage/current/conductor size	CSA	600 V/10 A/22...10 AWG

300 V/10 A/22...10 AWG
600 V/10 A/22...10 AWG

600 V/30 A/22...8 AWG

600 V/63 A/14...6 AWG

600 V/25 A/22...8 AWG

Ordering data

Version		Qty.		Qty.
KrG		Qty.		Qty.
KrG		Qty.		Qty.

0248920000 ³⁾ 20 0667520000 ³⁾ 20
0297520000 ⁴⁾ 20 0328920000 ⁴⁾ 20

0321320000 20 0501820000 20

0359420000 20 0502120000 20

0206820000 20 1368720000 20

End plate/partition (thickness mm)

Type	Cat. No.	Qty.
PA (2.5)	0191320000	
HP for		
TW (2.0)	0607000000	

Type	Cat. No.	Qty.
TW HP (2.0)	0607000000* 20	

Neozed D 01

Type	Cat. No.	Qty.
TW HP (2.0)	0607000000* 20	

Neozed D 02

Type	Cat. No.	Qty.
TW HP (2.0)	0607000000* 20	

Diazed E 16

Type	Cat. No.	Qty.
TW HP (2.0)	0607000000* 20	

Cross-connection



Fixing screws for cross-connections

Fuse inserts

1 1/4" x 1/4"	Nominal current (A):	0.5 fast	E 0.5 A	0533800000
		1.0 fast	E 1 A	0525500000
		2.0 fast	E 2 A	0294500000
		3.0 fast	E 3 A	0295700000
		5.0 fast	E 5 A	0294600000
		7.0 fast	E 7 A	0295800000
		10.0 fast	E 10 A	0293900000

Fuse insert	
Amp. Colour Cat. No. Qty.	
P 14/2 prk	0138000000 50
P 14/4 brown	0138100000 50
P 14/6 green	0328600000 50
P 14/10 red	0328700000 50

QL 2	0328000000 20
QL 3	0328100000 20
QL 4	0328200000 20
QL 10	0339000000 20

QL 2	0207800000 20
QL 3	0207900000 20
QL 4	0208000000 20
QL 10	0338900000 20

QL 2	0207800000 20
QL 3	0207900000 20
QL 4	0208000000 20
QL 10	0338900000 20

G fuse inserts 5 x 30 mm (500 V~/0.032...6.3 A).

Available from Wickmann-Werke GmbH, Annastr. 113, 58453 Witten, Germany, Phone ++492302/6620

D fuse inserts

Rated voltage 400 V	
E 14/2	0137400000 10
E 14/4	0137500000 10
E 14/6	0328300000 10
E 14/10	0328400000 10
E 14/16	0328500000 10

Rated voltage 400 V	
E 18/20	0361300000 10
E 18/25	0361400000 10
E 18/35	0361500000 10
E 18/50	0361600000 10
E 18/63	0361700000 10

Rated voltage 500 V	
E 10 A	0208500000 25
E 16 A	0208600000 25
E 20 A	0208700000 25
E 25 A	0208800000 25

Rated voltage 500 V	
P 16/10 red	0208900000 100
P 16/16 grey	0209000000 100
P 16/20 Blue	0209100000 100

Screw cap (spare)

red	SK (5 x 30)	0282000000 20
black	SK (1/4"x1 1/4")	0428900000 20

SK	0339410000 20
----	---------------

SK	0359310000 20
----	---------------

SK	0284110000 20
----	---------------

Marking tags

Print	DEK	Standard
-------	-----	----------

DEK 5	see "Accessories"
-------	-------------------

DEK 5	see "Accessories"
-------	-------------------

DEK 5	see "Accessories"
-------	-------------------

DEK 5	see "Accessories"
-------	-------------------

Mounting rails, end brackets, further marking material see "Accessories"

*only for TS 32

** Also for 440 V- with neozed marina fuse
*** Current for overload up to 10 A, for short circuit up to 25 A

³⁾ For fuse inserts 1 1/4 x 1/4" DEF 63
⁴⁾ For fuse inserts 5 x 30