



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Special Products



ATO® Resistor

Part Number: 02400100_ series

Specifications

Operating Temp.: -20°C to +85°C
Resistor Value: Optional
Power Rating: 1/4 W Max
Body Material: Thermoplastic
Term. Material: C.R.S. (Ni/Zn Plated)
Term. Retention: 25 N



ATO® Diode Part Number: 02400103_ (Z = 1500 / LXN = 50)

1 A Diode in ATO® size housing. The cathode connector is rotated 90°

1-A-Diode in ATO®-Größe mit 90°-abgewinkeltem Kathodenanschluss.

Operating Temp.: -40°C to +85°C
Diode Rating: 1.0 A
Max P.I.V.: Optional
Body Material: Thermoplastic
Term. Material: C.R.S. (Ni/Zn Plated)
Term. Retention: 25 N



MINI® Resistor

Part Number: 02400100_ series

Operating Temp.: -40°C to +85°C
Resistor Value: Optional
Power Rating: 1/4 W Max
Body Material: Thermoplastic
Term. Material: C.R.S. (Ni/Zn Plated)
Term. Retention: 25 N



MINI® Diode

Part Number: 02400113_ (P= 2000 / LXN = 50)

Operating Temp.: -40°C to +85°C
Diode Rating: 1.0 A
Max P.I.V.: Optional
Body Material: Thermoplastic
Term. Material: C.R.S. (Ni/Zn Plated)
Term. Retention: 25 N



ATO® Shunt

Part Number: 02400094P (2000 pcs)

Operating Temp.: -40°C to +125°C
Maximum Continuous Load Rating: 35A
Body Material: Thermoplastic (UL 94V0 Rated)
Term. Material: Brass Tin Plated



MINI® Shunt

Part Number: 0297900.WXNV (3000 pcs)

MINI® size shunt for continuous load up to 20A.

Shunt in MINI®-Bauform für Dauerlasten bis 20A.

Operating Temp.: -40°C to +125°C
Maximum Continuous Load Rating: 20A
Body Material: Thermoplastic (UL 94V0 Rated)
Term. Material: Zinc Silver Plated



JCASE® Shunt

Part Number: 0495900.Z

Operating Temp.: -40°C to +125°C
Maximum Continuous Load Rating: 50A
Body Material: Nylon
Term. Material: Copper