



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



NOTES:  
1. MATERIALS AND FINISHES(PLATING THICKNESS IN MICRO-INCHES):  
BODY - BRASS, NICKEL PLATING  
CONTACT - PHOSPHOR BRONZE, GOLD PLATING  
INSULATOR - PTFE,NATURAL  
  
2.WHEN CRIMPING CONTACT PIN TO CABLE, CRIMP WITH AMPHENOL TOOL 227-944 (M22520/5-01) AND DIE SET 227-1221-09, CAVITY 'B'(M22520/5-09,CLOSURE'B').227-1221-09 CAVITY 'B' HAS A HEX SIZE OF .068"  
  
3.WHEN CRIMPING FERRULE TO CABLE, CRIMP WITH AMPHENOL TOOL 277-944 (M22520/5-01) AND DIE SET 227-1221-09, CAVITY 'A' (M22520/5-09,CLOSURE'A').227-1221-09 CAVITY 'A' HAS A HEX SIZE .178"  
  
4.MAX. PANEL THICKNESS=6.35mm  
5.PACKAGE IN BAG 999-226,MARK PACKAGING BAG" R 5A 500V"  
6.ASTERISK (\*) INDICATES CABLE ENTRY DIM'S

THIRD ANGLE PROJ.

REVDESCRIPTIONDATEECOAPPR  
V SYNCH THE DRAWING WITH DANBURY\RD-DM11061601R323-Jun-1148640RM

15,06  
[.593]

2,54  
[.100]

6,35  
[.250]

3,96  
[.156]

RECOMMENDED  
CABLE STRIPPING DIM'S

$\varnothing 12,7^{+0,07}_{-0,00}$   
[.500<sup>+.003</sup><sub>-.000</sub>]

11,91<sup>+0,12</sup><sub>-0,00</sub>  
[.469<sup>+.005</sup><sub>-.000</sub>]

RECOMMENDED  
MOUNTING HOLE DIM'S  
SCALE 2.500

SCALE 1.500

CUSTOMER OUTLINE DRAWING  
ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: <0.5mm ± 0.05mm    0.5 - 6mm ±0.1mm    6 - 30mm ±0.2mm    30 - 120mm ± 0.3mm    ANGLES ±1°  NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	MATERIAL -	DRAWN R.MAO	DATE 23-Jun-11	TITLE QUICK CRIMP BNC BULKHEAD JACK FOR CABLE RG161/U, RG187/U , RG179/U		Amphenol RF <a href="http://www.amphenolrf.com">www.amphenolrf.com</a>	
	REFERENCE AND CONFIGURATION LEVEL: □□□□	ENGINEER D.ROYCE	DATE 8/11/89				
	FINISH	APPROVED S.HSIEH	DATE 23-Jun-11	SCALE: 4.0:1.0 SHEET 2 OF 2		DRAWING NO. 31-245	
		CAD FILE		DWG SIZE B	REV V	ITEM NO. 31-245	
						PART NO. 31-245	