

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







NOTES:	THIRD ANGLE PROJ.	$\oplus \ominus$	REVIS	SIONS		
1. MATERIALS AND FINISHES: BODY — BRASS, NICKEL PLATING		REV A	DESCRIPTION RELEASE TO MFG		TE ECO	APPR
CONTACT — PHOSPHOR BRONZE, GOLD PLATING INSULATOR — PTFE, NATURAL		В	REDRAWN, ADD COD, UPDATED N	OTES 4/29,	11 48522	SH
2. ELECTRICAL:						
B. FREQUENCY RANGE: DC 0-4 GHz	.593 ±.010					
C. DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS, MIN.  3. MECHANICAL: 250 ±.010	)  -					
A. DURABILITY: 500 CYCLES MIN.						
B. TEMPERATURE RANGE: - 65°C to +165°C  4. SOLDER CONTACT TO CABLE						
WHEN CRIMPING CONTACT TO CABLE, CRIMP WITH AMPHENOL TOOL						
227-944 (M22520/5-01) AND DIE SET 227-1221-11, CAVITY 'B'						
(M22520/5-11, CLOSURE 'B') 5. WHEN CRIMPING FERRULE TO CABLE, CRIMP WITH AMPHENOL TOOL	RECOMMENDED .					
227-944 (M22520/5-01) AND DIE SET 227-1221-11, CAVITY 'A'	CABLE STRIPPING DIM'S					
(M22520/5-11, CLOSURE 'A')						
		r ø.043			<del></del>	
		\$.0±3			1045	
ø.563		Ø.083	<u></u>		Ø.245	
		1				
	.463 REF —					
			.500			
	[* / /					
569 REF	1					
1.111 REF. — Ø.257	Ø.221 <del></del>					
		\				
STAMP "AMPHENOL 31-5705"	•					
STAMI AMITTENDE ST-5705	500					
	.500 —	<u> </u>				
	FOR USE ON PLENU	JM CABLE				
			CUSTON	<b>ER OUTLINE</b>	DRAWIN	IG
			ALL OTHER S	HEETS ARE FOR INTERNA	USE ONLY	
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: MATERIAL 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES		DATE TITLE 25/11 BNC	REVERSE POLARITY	Amphe	nol RF	
±.015 (0,381 mm) ±.005 (0,127 mm) ±1°	ENGINEER	DATE (OM)	N-SPECTRA INTERFACE	Danbury CT USA, Tainan www.amp	Taiwan, Shenzh ienolrf.com	nen China
NOTICE — These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or		DESIDATE RG58	GN) CRIMP PLUG FOR 3 & 141/U CABLE	DRAWING NO. 31-5705		
not to be regarded by implication or otherwise in any manner licensing, granting	K. CAPOZZI 4/2	29/11 SCALE: 3	SHEET 2 OF 2	ITEM NO. 31-5705		
rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to	CAD FILE	DWG SI	ZE CODE ID REV - 74868 <b>B</b>	PART NO. 31-5705		
or disclosed by said drawings, specifications, or other data.			/ 4000 B	01 0700		