

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







NOTES:

I. MATERIALS AND FINISHES:

BODY, RETAINER RING & HEX NUT - BRASS , NICKEL PLATING CONTACT - PHOSPHOR BRONZE, GOLD PLATING FERRULE - COPPER ALLOY, NICKEL PLATING LOCKWASHER - PHOSPHOR BRONZE, NICKEL PLATING

INSULATORS (X2) - PTFE

GASKET - SILICONE RUBBER, COLOR RED

2. ELECTRICAL:

A. IMPEDANCE: 75 OHM
B. FREQUENCY RANGE: DC - 4 GHz

C. D.W.V.: 500 VRMS, MIN.

3. MECHANICAL:

A. DURABILITY: 500 CYCLES MIN.
B. TEMPERATURE RANGE: -65° C TO +165° C

4. CUSTOMER NOTE: WHEN SOLDERING CONTACT TO CABLE, USE LEAD FREE SOLDER.

5. WHEN CRIMPING CONTACT PIN TO CABLE, CRIMP WITH AMPHENOL TOOL 227-944(M22520/5-01)AND DIE SET 227-980-2 CAVITY "B".


6. WHEN CRIMPING FERRULE TO CABLE, CRIMP WITH AMPHENOL TOOL 227-944(M22520/5-01) AND DIE SET 227-980-2 CAVITY "A"

7. PACKAGING:

A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL, 31-70016, AND DATE CODE"

Ø 12.83 [.505] 5.61 MIN.

RECOMMENDED MOUNTING PANEL DIMENSIONS SCALE 2.500




[.221]

RECOMMENDED CABLE STRIPPING DIMENSIONS SCALE 4.000


or disclosed by said drawings, specifications, or other data.



	REVISIONS			
REV	DESCRIPTION	DATE	ECO	APPR
Α	OFFICIAL ENG. RELEASR TO MFG.	- Ju - 85	31555	KS
В	31-11591-1 WAS 31-11591	I 4 - Sep - 85	32092	P.M
С	NOTE 3 WAS GRADE"D" PLATING	16-Feb-88	34866	RM
D	SYNC ARF AND ARFA DRAWING; LOCKWASHER AND NUT WERE CHANGED	-Ju -	48635	DH



SCALE 1.500



CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

PART NO.31-70016

REV

 \mathbb{D}

ONLEGO OTHERWINE OF LOTT TED, DIT			
<0.5mm 0.5 - 6mm	6 - 30mm 30	- 120mm ANGLES	
		0.3mm ±1°	
NOTICE - These drawings, specificati	ons, or other data	(I) are, and remain t	h e
property of Amphenol corp. (2) must			
confidential and not to be disclosed			
are given by Amphenol Corp. the fun			
other data by Amphenol Corp., or to			
not to be regarded by implication o			
rights to permitting such holder or product, process or design, patented			
product, process or design, parented	or officials to, find t	. Illay ili aliy way be ie	Turcu to

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE:

MATERIAL SEE NOTE I	DRAWN I.XU	DATE 20 - Jun - II
- SEE NOTE I	ENGINEER RICHER	DATE 12-Apr-02
REFERENCE	APPROVED	DATE
EAR 112-972850-50	D.HU	-Ju -
	CAD FILE	
FINISH	/PDMLINK/31-70016-JA	

	TITLE
_	BNC BULKHEAD JACK
	BNC BULKHEAD JACK 75 OHM FOR RG 179/U CABLE
	RG 179/U CABLE
	SCALE: 4.0:1.0 SHEET 2 OF 2

DWG SIZE

Danbury CT USA, Tainan, Taiwan, Shenzhen, China www.amphenolrf.com
DRAWING NO. 31-70016
ITEM NO. 31-70016

Amphenol RF