



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us









Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Disconnect Terminals

Disconnect Terminals		DKT 4		DKT 4 V			
							
							
		Lever & Feed Through		Dual Level			
Terminal Block Selection Data							
Available Options		Version					
With 2 StB test points KrS PA Beige PA		0327860000 0327960000		1304860000 1304960000			
		0687360000 0687460000					
Dimensions							
Width / Length / Height mm (in.)		for TS 32		6/65/70 (.23/2.56/2.76)		6/65/56.5/70 (.23/2.56/2.76)	
		for TS 35		6/65/70 (.23/2.56/2.76)		6/65/56.5/70 (.23/2.56/2.76)	
Insulation stripping length		mm (in.)		9 (.35)		9 (.35)	
Technical Data							
Rated voltage / rated current / wire size		UL	300 V / 10 A / #22...12 AWG		300 V / 10 A / #22...12 AWG		
		CSA	300 V / 10 A / #26...12 AWG		300 V / 10 A / #26...12 AWG		
		VDE	380 VAC / 10 A / 4 mm²		380 VAC / 10 A / 4 mm²		
Torque		Nm (lb. in.)	0.6 / 0.5 StB (8.0 / 4.5 StB)		0.6 / 0.5 StB (8.0 / 4.5 StB)		
Clamping screw		M	3		3		
Selected Accessory Data†							
End Plate (thickness mm)		Type	Part No.	Type	Part No.		
		Beige PA	AP (1.5) 0687560000	AP (1.5)	0687560000		
		Blue PA					
		KrG					
		KrS					
Partition (thickness mm)							
		PA					
		KrG					
		KrS					
		HP	TW (2.0)  0607000000	TW (2.0) 	0607000000		
Jumpers							
		Final number indicates number of poles. See the Accessories Section for more information. When using QB, maximum conductor connection is 2.5 mm².		QB 2	0482700000	QB 2	0482700000
				QB 3	0482800000	QB 3	0482800000
				QB 4	0482900000	QB 4	0482900000
				QB 75 bare*	0526400000	QB 75 bare*	0526400000
		Connection sleeve					
		Fixing screw					
		Lock washer					
		Insulation sleeve	IP 75 0526700000	IP 75	0526700000		
Plugs							
		Lock-out device	WTR/SAKR 9525900000				
		Test plug	PS 2.3 0180400000	PS 2.3	0180400000		
		Socket					
		Diode plug without diode					
		Diode plug with diode 1N4007					
		Disconnecter plug (spare)					
Marking Tags							
Print							
Note: Part numbers are shown for a single card of pre-printed tags numbered 1-50.		Consecutive horizontal	DEK 5/6 0468660001	DEK 5/6	0468660001		
		Consecutive vertical	DEK 5/6 0468760001	DEK 5/6	0468760001		

[‡]See Accessories section for additional information.
*Without DLS