



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Axial Lead Fuses

Subminiature

RoHS PICO® II Time Lag Fuse 472 Series



- The PICO® II time-lag fuse is designed for applications that require moderate inrush withstand and has a very low fuse resistivity.
- For additional inrush withstand, consult the 473 Series.

ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Opening Time
100%	4 hours, Minimum
200%	120 seconds, Max.

AGENCY APPROVALS: Recognized under the Components Program of Underwriters Laboratories.

AGENCY FILE NUMBERS:

INTERRUPTING RATINGS:

0.5 through 3 amperes – 50 amperes at 125 VAC and VDC

3.5 through 5 amperes – 50 amperes at 125 VAC

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature: -55°C to 125°C

Shock: MIL-STD-202, Method 213, Test Condition I (100 G's peak for 6 milliseconds).

Vibration: MIL-STD-202, Method 201 (10-55 Hz); Method 204, Test Condition C (55-2000 Hz at 10 G's Peak).

Moisture Resistance: MIL-STD-202, Method 106.

PHYSICAL SPECIFICATIONS:

Materials: Encapsulated, Epoxy-Coated Body; Solder Coated Copper Wire Leads, RoHS Compliant Product: Pure Tin coated copper Wire leads.

Flammability Rating: UL 94V0

Soldering Parameters:

Wave Solder — 260°C, 10 seconds maximum.

Solderability: MIL-STD-202, Method 208

Lead Pull Force: MIL-STD-202, Method 211, Test Condition A (will Withstand a 7lb. Axial pull test).

ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating	Nominal Resistance Cold Ohms	Nominal Melting I ² T A ² Sec.
0472 .500	1/2	125	0.17445	0.193
0472 001.	1	125	0.07850	0.938
0472 01.5	1.5	125	0.03917	2.408
0472 002.	2	125	0.02507	4.236
0472 02.5	2.5	125	0.02093	7.084
0472 003.	3	125	0.01866	9.360

