



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832











Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Direct Mount Terminals

Feed Through

	ADK 1		ADK 1 F ADK 3 F		MK 2/12	MK 1/3...22
						
Available Options (thickness mm) For Sheet Metal Version	1.5	2.5	1.5	2.5	Part No.	Part No.
PA	0303860000	0301060000	0476060000	0478660000		
3 pole KrG						0261620000
12 pole KrG						0261820000
12 pole PA					0241460000	
22 pole KrG						0301920000
All types except ADK 1 FT and MK 1/3... internal pin 0.8 x 2.8						
Dimensions						
Width / Length / Height with pins	mm (in.)	6/22/36.5 (.236/.87/1.44)	6/22/36.5 (.236/.87/1.44)	86/15/23 (2.68/.59/.91)	See table below	
Length of solder lug/pin	mm (in.)	8.4 (.33)	8.5/7.5 (.33/.30)	8 (.32)	5 (.20)	
Insulation stripping length	mm (in.)	9 (.35)	11 (.43)	5 (.20)	6 (.24)	
Technical Data						
Rated voltage / rated current / wire size	UL	300 V / 16 A / #22...12 AWG	300 V / 15 A / #26...14 AWG	300 V / 10 A / #24...12 AWG	300 V / 10 A / #24...12 AWG	
	CSA	300 V / 10 A / #26...12 AWG	300 V / 10 A / #22 ...14 AWG	300 V / 10 A / #24...12 AWG	300 V / 10 A / #22...16 AWG	
	VDE	380 VAC / 16 A / 4/1.5 mm ²	380 VAC / 20 A / 2.5/1.5 mm ²	6 VAC / 20 A / 2.5/1.5 mm ²	380 VAC / 20 A / 2.5/1.5 mm ²	
Torque	Nm (lb. in.)	0.5 (5.0)	0.9 (8.0)	0.4 (4.0)	0.4 (4.0)	
Clamping screw	M	3	2.5	2.5	2.5	
End Plate (thickness mm)	Type	Part No.	Type	Part No.	Dimensions	
	PA	AP (3) 0476260000	AP (3)	0476260000	MK 1/3	
	EP		AP (3)	0360000000		
Spacer (thickness mm)					MK 1/12 ...22	
						
Test Plugs / Sockets						
	PS 2.3	0180400000				
Fuse Pin / Insulating Sleeves / Expansion Rivet					Type Part No.	
	SST 1.3	0306600000	SST 1.3	0306600000		
	IH 2.8	0386060000	IH 2.8	0386060000		
					SN 0200100000	
Marking Tags	Print					
Note: Part numbers shown are for a single card of pre-printed tags numbered 1-50. For additional information, see Accessories section.	Consecutive horizontal	DEK 5/6 0468660001	DEK 5/6	0468660001	BSTb 10/12 0245700000	
	Consecutive vertical	DEK 5/6 0468760001	DEK 5/6	0468760001	BSTo 10/12 0245600000	
See Accessories section for end brackets, test plugs, additional marking material and accessories.						