

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









## 57316-5000 手動圧着工具 仕様書

57316-5000 HAND CRIMP TOOL PRODUCT SPECIFICATION

ATP-57316-5000JE 2005/02/25, Rev.- A 日本モレックス株式会社 Molex Japan Co., Ltd.

1.概要

Description

このツールは、モレックス社の圧着ターミナルに電線を圧着接続するために開発された、手動圧着工具 (ハンドソール)です。

ご使用前に、添付の手動圧着工具の取扱説明書 (S-0001)をお読み頂き、圧着作業手順と管理方法について熟知してから、本ハンドソールをご使用頂きますようお願い申し上げます。

This tool is a hand crimp tool, which is designed for crimp-connecting a wire to crimp a terminal of Molex.

Please take the time to read attached the operating manual (IS-0001) of Hand Crimp Tool, making sure you understand the crimping procedures and management method described it before attempting to operate this hand tool.

### 2. 仕様

**Specifications** 

1) 工具名称: 57316- 5000 手動圧着工具 Tool name: 57316-5000 Hand Crimp Tool

2) 工具型番: 57316- 5000 Tool number:

3) 外形寸法と重量: 230 (横幅 × 70 (奥行き × 15 (厚さ)mm、約 400 gf

Outer dimensions and weight: 230 (width) x 70 (depth) x 15 (thickness) mm, Approx. 400gf

4) 管理方法: 圧着部引張強度(詳細は該当圧着仕様書に記載)

Management method: Crimp strength (Details are described to the corresponding

crimp specification)

#### 5) 適合ターミナルと適合電線:

Applicable terminal and wire:

ターミナル番号 Terminal number	適合電線サイズ Applicable wire size (AWG)	適合被覆外径 Applicable insulation outer diameter (mm)	絶縁被覆ストリップ寸法 Wire insulation strip length (mm)
50397 50398	#26-28	1.1-1.4	2.6-3.1
50397 50398	#22-24	1.4 -1.7	2.6-3.1

### 3. 工具外観

**Tool Appearance** 



57316-5000

