



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# PIN RECEPTACLES

**FOR .015" - .020" DIAMETER PINS (#11 CONTACT)  
AND .015" - .022" DIAMETER PINS (#21 CONTACT)  
(SEE SPECIFIC CONTACT RANGE ON PAGE 251)**

<p><b>8467</b> 8467-0-15-XX-21-XX-04-0 Hex press-fit in .036 plated through-hole</p>	<p><b>6192</b> 6192-0-15-XX-21-XX-04-0 Square press-fit in .032 plated through-hole</p>	<p><b>9553</b> 9553-0-15-XX-X1-XX-04-0 Hex press-fit in .041 plated through-hole</p>	<p><b>5531</b> 5531-0-15-XX-21-XX-10-0 Hex press-fit in .041 plated through-hole</p>
<p><b>7553</b> 7553-0-15-XX-11-XX-10-0 Hex press-fit in .041 plated through-hole</p>	<p><b>9407</b> 9407-0-15-XX-11-XX-10-0 Solder mount in .040 min. mounting hole</p>	<p><b>9462</b> 9462-0-15-XX-21-XX-04-0 Hex press-fit in .043 plated through-hole</p>	<p><b>1147</b> 1147-0-18-XX-21-XX-10-0 Press-fit in .043 min. mounting hole Accepts wire sizes up to .014" dia.</p>
<p><b>3061</b> 3061-0-19-XX-21-XX-10-0 Wire Crimp Termination. Accepts wire sizes 28 AWG Max. / 32 AWG Min.</p>	<p><b>0579</b> 0579-0-15-XX-X1-XX-10-0 Press-fit in .040 mounting hole</p>	<p><b>8874</b> 8874-0-15-XX-11-XX-10-0 Bottom entry surface mount See page 152 for application details</p>	<p><b>0613</b> 0613-0-15-XX-21-XX-10-0 Press-fit in .047 mounting hole</p>

## SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Inches

**Tolerances On:** Lengths: ±.005

Diameters: ±.002

Angles: ± 2°



**ORDER CODE:** XXXX - X - 1X - XX - XX - XX - XX - 0

**BASIC PART #**

**SPECIFY SHELL FINISH:**

01 200 μ" TIN/LEAD OVER NICKEL

◆ 80 200 μ" TIN OVER NICKEL (RoHS)

◆ 15 10 μ" GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

02 100 μ" TIN/LEAD OVER NICKEL

◆ 84 100 μ" TIN OVER NICKEL (RoHS)

◆ 27 30 μ" GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#11 or #21 CONTACT (DATA ON PAGE 251)**

(For alternate contact choices, see group A on page 248)

