imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



echnic	al Data Sheet		Rose	enberge
PC-N 50 Ω				
otents	<image/>	Rosenberge RPC-3.50 MODEL 03CK020-180	SN DUU	
ntents	Device	RPC-3.50 MODEL 03CK020-150	SN DUU	Calibration Option ^a
		cure shows similar calibr	ration kit	
20 dB /	Device	cure shows similar calibr	ration kit	Option ^a
20 dB / 40 dB /	Device Attenuator plug/jack	Pert number 05AS122-K20S3	ration kit QTY 1	Option ^a FC FC
40 dB / Mismat	Device Attenuator plug/jack Attenuator plug/jack	Part number 05AS122-K20S3 05AS122-K40S3	ration kit QTY 1 1	Option ^a FC

See "Declaration of calibration options" for explanation. a.

This Verification Kit is designed as an electrical verification standard. Reference measurement values (calibration results) for transmission and reflection are included. Connected to a calibrated VNA the actual measured transmission and reflection values can be compared to the reference measurement values and the quality of the VNA calibration can be evaluated.

Rosenberger Hochfrequenztechnik GmbH & Co. KG	Tel. : +49 8684 18-0	Page
P.O.Box 1260 D-84526 Tittmoning Germany	Fax : +49 8684 18-499	
www.rosenberger.de	Email : info@rosenberger.de	1/3

RPC-N 50 Ω

05CK050-150

Documentation

This kit is delivered with

- USB-Stick
 With S2n data file of the
 - With S2p data file of the reference measurement values. Calibration Certificate as PDF-file.
- Kit Info Card Handling precautions.
- Calibration Certificate
 Details see "Declaration of calibration options".
- Operating Manual

Electrical specifications

This specification covers electrical key values for the main items of the verification kit. Specific datasheets are available for each component among the part number.

Device	Frequency	Parameter	Specification
20 dB Attenuator	DC to \leq 4 GHz	Return Loss	≥ 32 dB
	> 4 GHz to \leq 18 GHz	Return Loss	≥ 26 dB
	DC to \leq 4 GHz	Insertion Loss	20 dB ± 0.30 dB
	> 4 GHz to \leq 18 GHz	Insertion Loss	20 dB ± 0.50 dB
40 dB Attenuator	DC to \leq 4 GHz	Return Loss	≥ 32 dB
	> 4 GHz to \leq 18 GHz	Return Loss	≥ 23 dB
	DC to \leq 4 GHz	Insertion Loss	40 dB ± 0.50 dB
	> 4 GHz to \leq 18 GHz	Insertion Loss	40 dB ± 1.00 dB
25 Ω Mismatch Airline		Outer conductor: Diameter Length Center Conductor: Diameter 50 Ω section Diameter 25 Ω section Length total Length 25 Ω section	7.000 mm nominal 100.00 mm nominal 3.040 mm nominal 4.615 mm nominal 100.00 mm nominal 75.00 mm nominal
50 Ω Airline		Diameter	3.040 mm nominal
Center Conductor		Length	100.00 mm nominal

Rosenberger Hochfrequenztechnik GmbH & Co. KG	Tel. : +49 8684 18-0	Page
P.O.Box 1260 D-84526 Tittmoning Germany	Fax : +49 8684 18-499	
www.rosenberger.de	Email : info@rosenberger.de	2/3

Technical Data Sheet

RPC-N 50 Ω

Rosenberger

05CK050-150

Declaration of calibration options

Factory Calibration

Standard delivery for this verification standard includes a Factory Calibration. The Calibration Certificate issued reports individual calibration results, traceable to national / international standards. A S2p data file with the reference measurement values is included.

Accredited Calibration

Not available.

For further, more detailed information see application note AN001 on the Rosenberger homepage.

Calibration interval

Recommendation

12 months

Recommended accessories

- Rosenberger Test Port Adaptor
- Rosenberger Gauge Kit 05GK0KS-010
- Rosenberger VNA Test cable kit and Microwave Cable Assemblies

For further, more detailed information please visit our homepage <u>www.rosenberger.com</u>.

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date		Rev.	Engineering change number	Name	Date
Herbert Babinger	10.08.15	Martin Moder	12.08.15		a00	15-s228	A. Youmsi Mouafo	12.08.15
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany				-	l. : +49 8684 18-0 x : +49 8684 18-499		Page	
www.rosenberger.de				En	nail : <u>info@rosenberger.de</u>		3/3	

RF 35/05.10/6.