



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [62201-8644](#)
Status: **Active**
Description: Backplane Module Installation Press-In Tool

Documents:
[RoHS Certificate of Compliance \(PDF\)](#)


General

Product Family	Application Tooling
Series	T3002
Comments	See Tooling Specification (PDF) Above
Function	Insertion
Geographic Area	Global
Level of Automation	Manual
More Detailed Tech Information	applicationtooling@molex.com
Product Name	Impact™
Survey	www.molex.com//review/apptool_survey.html
Tool Type	Handtool
UPC	800756963723

Material Info

Reference - Drawing Numbers

Application Tooling Documents [ATS-622018644](#), [TM-622018799](#)



Series

image - Reference only

EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Low-Halogen Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[T3002Series](#)

Use With

Impact™ Backplane Signal Module, [76155 Series](#)

Application Tooling | **FAQ**
Description | **Product #**

Impact™ 100 Ohm 4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Unguided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	0761551607
Impact™ 100 Ohm 4 Pair Vertical Backplane Header, 1.90 by 1.35mm	0761551603

Pitch, Unguided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
4.50mm, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551604
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551605
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551606
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
4.50mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761551608
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761551613
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Left Endwall, 16
Columns, 192
Circuits, Pin Length
4.50mm, Plated

Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551614
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Left Endwall, 16
Columns, 192
Circuits, Pin Length
4.90mm, Plated

Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551615
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Left Endwall, 16
Columns, 192
Circuits, Pin Length
5.50mm, Plated

Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551616
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Left Endwall, 16
Columns, 192
Circuits, Pin Length
4.50mm, Plated

Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761551617
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Left Endwall, 16
Columns, 192
Circuits, Pin Length
4.90mm, Plated

Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761551618
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Left Endwall, 16
Columns, 192
Circuits, Pin Length
5.50mm, Plated

Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761551623
4 Pair Vertical

Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Dual Endwall, 16
Columns, 192
Circuits, Pin Length
4.50mm, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551624
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Dual Endwall, 16
Columns, 192
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551625
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Dual Endwall, 16
Columns, 192
Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551626
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Dual Endwall, 16
Columns, 192
Circuits, Pin Length
4.50mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761551627
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Dual Endwall, 16
Columns, 192
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761551628
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Dual Endwall, 16
Columns, 192

Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761551633
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Right Endwall,
16 Columns, 192
Circuits, Pin Length
4.50mm, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551634
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Right Endwall,
16 Columns, 192
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551635
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Right Endwall,
16 Columns, 192
Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761551636
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Right Endwall,
16 Columns, 192
Circuits, Pin Length
4.50mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761551637
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Unguided,
Right Endwall,
16 Columns, 192
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free

Impact™ 100 Ohm	0761551638
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Unguided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
Impact™ 100 Ohm	0761553603
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	
Impact™ 100 Ohm	0761553604
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead-Free	
Impact™ 100 Ohm	0761553605
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	
Impact™ 100 Ohm	0761553606
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
Impact™ 100 Ohm	0761553607
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided,	

Open Endwall,
16 Columns, 192
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761553608
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Left Guided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761553618
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Left Guided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.39mm ,
Orientation Key A,
Lead-Free
Impact™ 100 Ohm 0761555603
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
4.50mm, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761555604
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761555605
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
5.50mm, Plated

Through Hole
Dimension 0.46mm,
Lead-Free
Impact™ 100 Ohm 0761555606
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
4.50mm, Plated

Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761555607
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
4.90mm, Plated

Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761555608
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
5.50mm, Plated

Through Hole
Dimension 0.39mm,
Lead-Free
Impact™ 100 Ohm 0761555618
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Open Endwall,
16 Columns, 192
Circuits, Pin Length
5.50mm, Plated

Through Hole
Dimension 0.39mm ,
Orientation Key A,
Lead-Free
Impact™ 100 Ohm 0761557603
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Left Guided,
Right Endwall,
16 Columns, 192
Circuits, Pin Length
4.50mm, Plated

Through Hole
Dimension 0.46mm,
Lead-Free

Impact™ 100 Ohm	0761557604
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead-Free	
Impact™ 100 Ohm	0761557605
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	
Impact™ 100 Ohm	0761557606
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
Impact™ 100 Ohm	0761557607
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
Impact™ 100 Ohm	0761557608
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
Impact™ 100 Ohm	0761557618
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided,	

Right Endwall,
16 Columns, 192
Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.39mm ,
Key Orientation A,
Lead-Free
Impact™ 100 Ohm 0761558604
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Left Endwall, 16
Columns, 192
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.46mm,
Tin (Sn) Lead (Pb)
Impact™ 100 Ohm 0761558605
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Left Endwall, 16
Columns, 192
Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.46mm,
Tin (Sn) Lead (Pb)
Impact™ 100 Ohm 0761558607
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Left Endwall, 16
Columns, 192
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Tin (Sn) Lead (Pb)
Impact™ 100 Ohm 0761558608
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Left Endwall, 16
Columns, 192
Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.39mm,
Tin (Sn) Lead (Pb)
Impact™ 100 Ohm 0761559603
4 Pair Vertical
Backplane Header,
1.90 by 1.35mm
Pitch, Right Guided,
Left Endwall, 16
Columns, 192
Circuits, Pin Length
4.50mm, Plated

Through Hole
Dimension 0.46mm,
Lead-Free

This document was generated on 04/04/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION