

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



The illustration shows version HDFKV 50 in gray

Panel feed-through terminal block, Connection method: Screw connection, Load current: 150 A, Cross section: 16 mm² - 50 mm², AWG 6 - 1/0, Width: 18.8 mm, Color: green/yellow



#### Key commercial data

Packing unit	11
Minimum order quantity	10 1
GTIN	4 017918 004675
Weight per Piece (excluding packing)	133.3 GRM
Custom tariff number	85369010
Country of origin	Greece

#### Technical data

#### General

Number of levels	1
Number of connections	2
Color	green/yellow
Insulating material	PA
Inflammability class according to UL 94	V0
Rated surge voltage	8 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-1
Nominal current I <sub>N</sub>	150 A



## Technical data

#### General

Nominal voltage U <sub>N</sub>	690 V
Open side panel	nein
Number of positions	1

#### Dimensions

Width	18.8 mm	
	10.0	

#### Connection data

Note	Terminal sleeve
Connection side	Level 1 ext. 1
Connection method	Screw connection
Note	Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.
Conductor cross section solid min.	16 mm²
Conductor cross section solid max.	50 mm <sup>2</sup>
Conductor cross section stranded min.	16 mm²
Conductor cross section stranded max.	50 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	6
Conductor cross section AWG/kcmil max	1/0
Conductor cross section stranded, with ferrule without plastic sleeve min.	10 mm <sup>2</sup>
Conductor cross section stranded, with ferrule without plastic sleeve max.	50 mm <sup>2</sup>
Conductor cross section stranded, with ferrule with plastic sleeve min.	10 mm <sup>2</sup>
Conductor cross section stranded, with ferrule with plastic sleeve max.	50 mm <sup>2</sup>
2 conductors with same cross section, solid min.	6 mm²
2 conductors with same cross section, solid max.	16 mm <sup>2</sup>
2 conductors with same cross section, stranded min.	10 mm <sup>2</sup>
2 conductors with same cross section, stranded max.	16 mm <sup>2</sup>
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	6 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	16 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	10 mm²
Stripping length	24 mm
Internal cylindrical gage	B10
Screw thread	M6
Tightening torque, min	6 Nm



#### Technical data

#### Connection data

Tightening torque max	8 Nm

#### Classifications

#### eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141134
eCl@ss 5.1	27141134
eCl@ss 6.0	27141134
eCl@ss 7.0	27141134
eCl@ss 8.0	27141134

#### **ETIM**

ETIM 2.0	EC001283
ETIM 3.0	EC001283
ETIM 4.0	EC001283
ETIM 5.0	EC001283

#### **UNSPSC**

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

## Approvals

#### Approvals

Approvals

 ${\sf CSA\,/\,UL\,\,Recognized\,/\,\,KEMA-KEUR\,/\,\,GOST\,/\,\,IECEE\,\,CB\,\,Scheme\,/\,\,GOST}$ 

Ex Approvals

Approvals submitted



## Approvals

#### Approval details

CSA (1)			
		В	С
mm²/AWG/kcmil	6	6	
Nominal current IN	125 A	125 A	125 A
Nominal voltage UN	600 V	600 V	600 V

UL Recognized <b>5</b>	
mm²/AWG/kcmil	6
Nominal current IN	150 A
Nominal voltage UN	600 V

KEMA-KEUR KETA		
mm²/AWG/kcmil	50	
Nominal current IN	150 A	
Nominal voltage UN	690 V	

GOST C

IECEE CB Scheme CB.	
mm²/AWG/kcmil	50
Nominal current IN	150 A
Nominal voltage UN	690 V




## Approvals

GOST 🕑

## **Drawings**

# Dimensioned drawing

#### Dimensioned drawing



© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com