Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!


## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832
Email & Skype: info@chipsmall.com Web: www.chipsmall.com
Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






NOTES:

1. MATERIALS:
   HOUSING: HIGH TEMPERATURE PLASTIC, UL 94V-0, COLOR: BLACK
   TERMINAL: COPPER ALLOY
   SHIELD: STEEL ALLOY
2. FINISH:
   TERMINAL: GOLD PLATING OVER 1.27 MICROMETER(50u") NICKEL IN CONTACT AREA,
   3.81 MICROMETER (150u") PURE TIN OVER 1.27 MICROMETER (50u") NICKEL AT SOLDERING AREA.
   BACK SHIELD: 3.81 MICROMETER (150u") BRIGHT TIN OVER 1.27 MICROMETER (50u") NICKEL OVER COPPER FLASH OVERALL.
   FRONT SHIELD: 1.27 MICROMETER (50u") SOLDERING NICKEL OVER COPPER FLASH OVERALL.
3. PRODUCT SPECIFICATION: PS-74320-001.
4. PACKAGING: PARTS ARE TO BE PACKAGED 40 PCS PER TRAY.
5. THE LOADED CIRCUITS SEE THE CHART.
6. THE DIMENSION SHOWN ON SHEET 1 REFLECT THE DVI-D SINGLE AND DUAL CHANNEL ASSEMBLY.
   THE DIMENSION SHOWN ON SHEET 2 REFLECT THE DVI-I ASSEMBLY.
   FOR ALL OTHER DIMENSION REFER TO SHEET 1.










FINISH

CHANGE FRONT SHELL
EC NO: SH2016-0197 2015/12/07
DRWN:XQZHANG 2015/12/07
CH'KD:XQZHANG 2016/01/18
APPR:AYIN
DESCRIPTION
REV
C

QUALITY SYMBOLS
$F_A$=0
$F_C$=0
$F_P$=0

| GENERAL TOLERANCES (UNLESS SPECIFIED) | mm | INCH |
|---|---|---|
| 4 PLACES | ± --- | ± --- |
| 3 PLACES | ± --- | ± --- |
| 2 PLACES | ± 0.25 | ± --- |
| 1 PLACE | ± 0.25 | ± --- |
| 0 PLACE | ± | ± |
| ANGULAR ± .5 ° | | |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 1:1
DESIGN UNITS: INCH
THIRD ANGLE PROJECTION

DRAWN BY: JCHIANG DATE: 00/05/12
CHECKED BY: MLIN DATE: 00/05/12
APPROVED BY: MLIN DATE: 00/05/12
MATERIAL NO.: SEE SHEET 2

TITLE: HIGH VOLUME DVI PLUG CONNECTOR FOR PCB MOUNT

molex

DOCUMENT NO.: SD-74323-005
SHEET NO.: 1 OF 3
SIZE: A3

| PART NO. | DESCRIPTION | LOAD CIRCUIT REF |
|---|---|---|
| 74323-2101 | DVI-D Au FLASH SINGLE CHANNEL | 1-3,6-8,9-11,14-16,17-19,22-24 WITH KEY |
| 74323-2103 | DVI-D Au FLASH DUAL CHANNEL | 1-24, WITH KEY |
| 74323-2131 | DVI-I Au FLASH SINGLE CHANNEL | 1-3,6-8,9-11,14-16,17-19,22-24 C1-C5 |
| 74323-2133 | DVI-I Au FLASH DUAL CHANNEL | 1-24,C1-C5 |
















SEE SHEET 1
EC NO: SH2016-0197 2015/12/07
DRWN:XQZHANG 2015/12/07
CH'KD:XQZHANG 2016/01/18
APPR:AYIN
DESCRIPTION
REV

QUALITY SYMBOLS
FA=0
FC=0
FD=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | mm | INCH |
|---|---|---|
| 4 PLACES | ± --- | ± --- |
| 3 PLACES | ± --- | ± --- |
| 2 PLACES | ± 0.25 | ± --- |
| 1 PLACE | ± 0.25 | ± --- |
| 0 PLACE | ± | ± |

ANGULAR ± .5 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 1:1
DESIGN UNITS: INCH
THIRD ANGLE PROJECTION

DRAWN BY: JCHIANG DATE: 00/05/12
CHECKED BY: MLIN DATE: 00/05/12
APPROVED BY: MLIN DATE: 00/05/12
MATERIAL NO.: SEE TABLE

TITLE: HIGH VOLUME DVI PLUG CONNECTOR FOR PCB MOUNT

molex

DOCUMENT NO.: SD-74323-005
SHEET NO.: 2 OF 3
SIZE: A3




RECOMMANDED PCB LAYOUT, PCB THICKNESS: 1.60 MM

| | | | | | |
|---|---|---|---|---|---|
| SEE SHEET 1<br>EC NO: SH2016-0197 2015/12/07<br>DRWN:XOZHANG 2015/12/07<br>CH'KD:XOZHANG<br>APPR:AYIN 2016/01/18<br>DESCRIPTION<br>REV C | QUALITY SYMBOLS<br>FA=0<br>FC=0<br>FP=0 | GENERAL TOLERANCES (UNLESS SPECIFIED)<br>mm / INCH<br>4 PLACES ± --- / ± ---<br>3 PLACES ± --- / ± ---<br>2 PLACES ± 0.25 / ± ---<br>1 PLACE ± 0.25 / ± ---<br>0 PLACE ± / ±<br>ANGULAR ± .5 °<br>DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | DIMENSION STYLE: MM ONLY<br>DRAWN BY: JCHIANG DATE: 00/05/12<br>CHECKED BY: MLIN DATE: 00/05/12<br>APPROVED BY: MLIN DATE: 00/05/12<br>MATERIAL NO.: SEE SHEET 2 | SCALE: 4:1<br>DESIGN UNITS: INCH<br>THIRD ANGLE PROJECTION<br>TITLE: HIGH VOLUME DVI PLUG CONNECTOR FOR PCB MOUNT<br>molex<br>DOCUMENT NO.: SD-74323-005<br>SHEET NO.: 3 OF 3<br>SIZE A3 |