

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## Clip, 5 x 20 mm, UR, Cover





Variant 2

## 500 VAC/DC · 10 A (UL/CSA)







#### Description

- Clip-material: bronze or brass
- Optional covers, see accessories

#### **Standards**

- UL 4248-1
- CSA C22.2 no. 4248.1

## **Approvals**

- UL File Number: E39328

#### Weblinks

pdf datasheet, html-datasheet, General Product Information, Packaging details, Approvals, CE declaration of conformity, RoHS, CHINA-RoHS, REACH, Distributor-Stock-Check, Accessories, Detailed request for product


## **Technical Data**

Fuse-Link	5 x 20 mm	
Mounting	PCB	
Attachment	Screw, rivet or THT	
Terminal	Solder THT	
Rated Voltage	500 VAC/DC	
Rated current	10A (UL/CSA)	
Admissible Ambient Air Temp.	-40 °C to 85 °C	
Climatic Category	40/085/21 acc. to IEC 60068-1	
Material: Terminals	see variants	
Unit Weight	0.55 g	
Storage Conditions	0°C to 60°C, max. 70% r.h.	
Product Marking	■, Approvals	

Soldering Methods	Wave
	Soldering Profile
Solderability	245°C / 3 sec acc. to IEC 60068-2-20,
	Test Ta, method 1
Resistance to Soldering Heat	260°C / 10 sec acc. to IEC 60068-2-20,
G	Test Tb, method 1A
Contact Resistance	< 10 mΩ at 20 mV

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in **General Product Information** 


## **Dimension**





Variants 0751.0052 and 0751.0062

Drilling holes variants 0751.0052 and 0751.0062





Variants 2 0751.0110 and 0751.0231

Drilling Diagram variants 2 0751.0110 and 0751.0231

## **All Variants**

Clip	Terminal	Material: Terminals	Order Number	
•	straight	Tin-Plated Bronze	0751.0052	
•	straight	Tin-Plated Brass	0751.0062	
•	kinked	Tin-Plated Brass	0751.0110	
•	kinked	Silver-Plated	0751.0231	

Most Popular.

Availability for all products can be searched real-time:http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Covers only for 0751.0052 and 0751.0062

Packaging Unit Bulk (1000 pcs.)

## Accessories

## Description



Cover OG, UHB, UH
Cover for Holder OG (Clip) 5x20, OG (Halter) 5x20, UH, UHB