

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









# Shrink sleeve - WMS 3,2 (EX5)RL - 0800320

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Shrink sleeve, Roll, white, Unlabeled, Can be labeled with: Thermomark W, Thermomark R, Thermomark X, Unperforated, Mounting type: Slide on, Cable diameter: 1-3.2 mm

The figure shows the WMS 12,7 (Ex20)R version

## Why buy this product

- Available in the form of continuous rolls and can be printed on both sides using the THERMOMARK W2 printer
- The shrink sleeves are automatically perforated or cut to the required length during the printing process
- ☑ UL 224 (125°C, 600 V, VW-1)
- ☑ CSA.C22.2 No. 198.1 (125°C, 600 V, VW-1)

## Key commercial data

| Packing unit           | 1                   |
|------------------------|---------------------|
| Minimum order quantity | 17                  |
| Catalog page           | Page 168 (CL2-2011) |
| GTIN                   | 4 046356 625906     |
| Custom tariff number   | 39173200            |
| Country of origin      | CHINA               |

### Technical data

## General

| Length (b)                      | 120 m                       |
|---------------------------------|-----------------------------|
| Width (a)                       | 5 mm                        |
| Color                           | white                       |
| Base element material           | polyolefine                 |
| Wipe resistance                 | DIN EN 61010-1 (VDE 0411-1) |
| Ambient temperature (operation) | -55 °C 125 °C               |
| Components                      | Halogen-free                |
| Material                        | Polyolefine                 |



## Shrink sleeve - WMS 3,2 (EX5)RL - 0800320

## Classifications

#### eclass

| eCl@ss 4.0 | 24190208 |
|------------|----------|
| eCl@ss 4.1 | 24190208 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27149103 |
| eCl@ss 6.0 | 27400401 |
| eCl@ss 7.0 | 27400401 |

#### etim

|          | ~        |
|----------|----------|
| ETIM 4.0 | EC001530 |

### unspsc

| UNSPSC 6.01   | 30211811 |
|---------------|----------|
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

## Accessories

#### Accessories

Ink ribbon - THERMOMARK-RIBBON 64-WMSE - 5145724



Ink ribbon, Length: 300000 mm, Width: 64 mm, Color: black

## Ink ribbon - THERMOMARK-RIBBON 64-WMSE BU - 5145737



Ink ribbon, Length: 300000 mm, Width: 64 mm, Color: blue

#### Ink ribbon - THERMOMARK-RIBBON 64-WMSE RD - 5145740



Ink ribbon, Length: 300000 mm, Width: 64 mm, Color: red



# Shrink sleeve - WMS 3,2 (EX5)RL - 0800320

## Accessories

Media hub - THERMOMARK-ERH 500 - 5146309



External media hub, for the THERMOMARK ROLL, for roll diameter of up to 500 mm

© Phoenix Contact 2012 - all rights reserved http://www.phoenixcontact.com