

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Label, highly flexible - EMLF (108XE)R SR - 0800551

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Label, highly flexible, Roll, silver, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X1.2, Mounting type: Adhesive, Lettering field: 110 x 40000 mm

The figure shows the white version

Product Features

- Labeling service: Phoenix Contact can custom-label all EMLF ... markers according to your requirements

- Highly flexible, soft PVC label that adapts well to uneven surfaces

Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|----------|
| Weight per Piece (excluding packing) | 1160.0 g |
| Custom tariff number | 39199000 |
| Country of origin | Germany |

Technical data

Dimensions

| Length (b) | 40000 mm |
|------------|----------|
| Width (a) | 108 mm |

Ambient conditions

| Ambient temperature (operation) | -40 °C 90 °C |
|---------------------------------|--------------------------------|
| Ambient temperature (assembly) | >8°C |
| Recommended storage conditions | 23 °C / 50 % relative humidity |

General

| Color | silver |
|-----------------|-----------------------------|
| Components | Silicone-free |
| Material | PVC |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |



Label, highly flexible - EMLF (108XE)R SR - 0800551

Technical data

General

| Number of individual labels | 1 |
|--|--|
| Number of individual labels per row | 1 |
| Adhesive | Acrylic |
| File number | UL-MH48542 / PC-019 (transparent foil) |
| Printability | Thermal transfer |
| Device | 5146477 THERMOMARK ROLL |
| | 5146723 THERMOMARK ROLL X1 |
| | 5146257 THERMOMARK S1.1 |
| | 5146231 THERMOMARK X1.2 |
| Ink ribbon | 5145384 THERMOMARK-RIBBON 110 |
| Test specification weathering-resistance | Following ISO 4892-2:2013-03 |
| Test duration | 96 h |
| Wipe resistance test result | Test passed |
| Salt spray test specification | DIN EN 60068-2-11:2000-02 |
| Test duration | 96 h |
| Salt spray testing result | Test passed |
| Alternating condensation climate with SO2 test specification | Following DIN 50018:2013-05 |
| Climate level | AHT 1.0 S |
| Cycles | 2 |
| Condensation test result | Test passed |
| Wipe resistance of test specification inscriptions | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result | Test passed |
| Foil strength | 50 μm |
| Marking mounting type | Adhesive |

Standards and Regulations

| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|
|-----------------|-----------------------------|

Classifications

eCl@ss

| eCl@ss 4.0 | 24190219 |
|------------|----------|
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27149129 |



Label, highly flexible - EMLF (108XE)R SR - 0800551

Classifications

ETIM

| ETIM 2.0 | EC000761 |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |

UNSPSC

| UNSPSC 6.01 | 30211811 |
|---------------|----------|
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

Phoenix Contact 2015 @ - all rights reserved http://www.phoenixcontact.com