# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





### Shrink sleeve - WMS 12,7 (60X20)RL YE - 0803107

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Shrink sleeve, Roll, yellow, unlabeled, can be labeled with: THERMOMARK W, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X1.2, Perforated, Lettering field: 60 x 20 mm



The illustration shows WMS 6,4 (30X10)R

#### **Product Features**

- 1 WMS ... shrink sleeves provide permanent and captive conductor and cable marking
- ☑ The sleeves are pre-assembled for optimum use of material
- The conductor to be marked is simply threaded through the sleeve and fixed by shrinking the sleeve
- ☑ The sleeves remain flexible after shrinking
- ☑ Up to four markers per sleeve are separated by perforations
- ☑ UL 224 (125°C, 600 V, all tubing)
- CSA.C22.2 No. 198.1 (125°C, 600 V, all tubing)

☑

#### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	12.0 GRM
Custom tariff number	39173200
Country of origin	China

#### Technical data

#### Dimensions

Length (b)	60 mm
Width (a)	20 mm

#### General

Color	yellow
Base element material	polyolefine
Components	Halogen-free
Material	Polyolefine



## Shrink sleeve - WMS 12,7 (60X20)RL YE - 0803107

#### Technical data

#### General

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	1000

#### Classifications

#### eCl@ss

eCl@ss 4.1	24190219
eCl@ss 5.1	27400401
eCl@ss 6.0	27400401
eCl@ss 8.0	27400401

#### ETIM

ETIM 4.0	EC000217
ETIM 5.0	EC001530

Phoenix Contact 2015  $\ensuremath{\mathbb{C}}$  - all rights reserved http://www.phoenixcontact.com