



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




# Label, highly flexible - MM-EMLF (EX18)R C1 YE/BK - 0803943

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Highly flexible label, continuous, cassette, yellow with black imprint, mounting type: adhesive, can be marked with THERMOFOX

## Key Commercial Data

|              |   |
|--------------|---|
| Packing unit | 1 STK   |
| GTIN         | <br>4 055626 212227 |
| GTIN         | 4055626212227   |

## Technical data

### Dimensions

|            |       |
|------------|-------|
| Length (b) | 8 m   |
| Width (a)  | 18 mm |

### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -20 °C ... 75 °C  |
| Recommended storage conditions  | 20°C/50% relative humidity. Storage in the original packaging is recommended. |

### General

|   |                                |
|---|--------------------------------|
| Color   | yellow                         |
| Components  | Free from silicone and cadmium |
| Material  | Vinyl polymer                  |
| Wipe resistance   | DIN EN 61010-1 (VDE 0411-1)    |
| RoHS compliant  | Yes                            |
| Adhesive  | Acrylic                        |
| Printability  | Thermal transfer               |
| Device  | 0803984 THERMOFOX              |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02           |
| Result  | Test passed                    |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03   |
| Test duration   | 96 h                           |
| Wipe resistance test result   | Test passed                    |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02      |

## Label, highly flexible - MM-EMLF (EX18)R C1 YE/BK - 0803943

### Technical data

#### General

|  |                                     |
|--|-------------------------------------|
| Test duration                                      | 96 h                                |
| Salt spray testing result                          | Test passed                         |
| Wipe resistance of test specification inscriptions | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result   | Test passed                         |
| Marking mounting type                              | Adhesive                            |

#### Standards and Regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

---

Phoenix Contact 2017 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>