



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Contactor marker - SS-3R 20X7 WH - 0807740

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Marker sheet, for Siemens SIRIUS 3R switchgear series, 40-section, 20 strips à 2 markers, labeling with M-PEN, CMS system or BMKT labels, lettering field: 20 x 7 mm

## Key commercial data

Packing unit	1
Minimum order quantity	10
Catalog page	Page 435 (CL-2005)
GTIN	 4 017918 156954
Weight per Piece (excluding packing)	9.7 GRM
Country of origin	GERMANY

## Technical data

### General

Note	Can be labeled with CMS
Length (b)	20 mm
Width (a)	7 mm
Color	white
Base element material	ABS
Inflammability class according to UL 94	V0
Wipe resistance	DIN 30646
Wipe resistance	DIN VDE 0611-1
Ambient temperature (operation)	-40 °C ... 80 °C
Material	ABS
Number of individual labels	40
Number of individual labels per row	2

## Classifications

### eclass

eCl@ss 4.0	24190218
eCl@ss 4.1	24190218
eCl@ss 5.0	27141137

## Contactor marker - SS-3R 20X7 WH - 0807740

### Classifications

#### eclass

eCl@ss 5.1	27141137
eCl@ss 6.0	27141137

#### etim

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC000761

#### unspsc

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410