

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









STP 5-3

Order No.: 0810562



http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=0810562

Triple marker carriers, snaps onto the three-level spring-cage terminal block ST 2.5-3L, labeled with ZB 5 or ZBF $\,$

Commercial data	
GTIN (EAN)	4 017918 877934
sales group	B108
Pack	100 pcs.
Customs tariff	85389099
Catalog page information	Page 338 (CL-2009)

Product notes

WEEE/RoHS-compliant since: 01/01/2003



http://

www.download.phoenixcontact.com Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Length (b)	32 mm
Height	26 mm
Width (a)	5 mm
Color	gray

STP 5-3 Order No.: 0810562

http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=0810562

Inflammability class acc. to UL 94	V2
Ambient temperature (operation)	-40 °C 100 °C
Components	free from silicone and halogen
Material	PA

Address

PHOENIX CONTACT Deutschland GmbH Flachsmarktstr. 8 32825 Blomberg,Germany Phone +49 5235 3 12000 Fax +49 5235 3 41200 http://www.phoenixcontact.de



© 2011 Phoenix Contact Technical modifications reserved;