



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




## Shrink sleeve - WMS 2,4 (25X5)R - 0816294

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Shrink sleeve, Roll, white, Unlabeled, Can be labeled with: Thermomark W, Thermomark R, Thermomark X, Perforated, Mounting type: Slide on, Cable diameter: 0.8-2.4 mm

### Key commercial data

Packing unit	1
Minimum order quantity	20
Catalog page	Page 554 (CL-2009)
GTIN	 4 046356 108492
Weight per Piece (excluding packing)	272.9 GRM
Country of origin	UNITED STATES

### Technical data

#### General

Length (b)	25 mm
Width (a)	5 mm
Color	white
Base element material	polyolefine
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Ambient temperature (operation)	-55 °C ... 125 °C
Components	Halogen-free
Material	Polyolefine
Number of individual labels	500

### Classifications

#### eclass

eCl@ss 4.0	24190219
eCl@ss 4.1	24190219
eCl@ss 5.0	27149103
eCl@ss 5.1	27149103
eCl@ss 6.0	27141137

# Shrink sleeve - WMS 2,4 (25X5)R - 0816294

## Classifications

etim

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC000761

unspsc

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

## Accessories

### Accessories

Ink ribbon - THERMOMARK-RIBBON 64-WMSE - 5145724



Ink ribbon, Length: 300000 mm, Width: 64 mm, Color: black

Ink ribbon - THERMOMARK-RIBBON 64-WMSE BU - 5145737



Ink ribbon, Length: 300000 mm, Width: 64 mm, Color: blue

Ink ribbon - THERMOMARK-RIBBON 64-WMSE RD - 5145740



Ink ribbon, Length: 300000 mm, Width: 64 mm, Color: red

Ink ribbon - THERMOMARK-RIBBON 55-WMSHF - 0827856



Ink ribbon, length: 300 m, width: 55 mm, print color: black (specifically for halogen-free shrink sleeves)

## Shrink sleeve - WMS 2,4 (25X5)R - 0816294

### Accessories

---

---

© Phoenix Contact 2012 - all rights reserved  
<http://www.phoenixcontact.com>