



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




## UC-TMF 4

Order No.: 0818166



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=0818166>

UniCard sheets, for labeling terminal blocks using a flat Zack marker strip groove, 120-section, can be labeled with BLUEMARK X1 and CMS-P1-PLOTTER, color: White

Commercial data	
GTIN (EAN)	
sales group	B102
Pack	10 pcs.
Customs tariff	39269097
Catalog page information	Page 482 (CL-2009)

### Product notes

WEEE/RoHS-compliant since:  
06/21/2007



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>General</b>	
Width (a)	4 mm
Color	white
Inflammability class acc. to UL 94	V2
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)

Ambient temperature (operation)	-40 °C ... 120 °C
Components	free from silicone and halogen
Pitch	4.2 mm
Material	PA
Number of individual labels	120
Number of individual labels per row	15
Pitch	4.2 mm

### Accessories

Item	Designation	Description
<b>General</b>		
5146105	P1 UC-MAG 4	Magazine, for CMS-P1-PLOTTER, for accommodating UC-TMF..., UC1-TMF..., UC-WMT...

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;