



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Marker carriers - CARRIER/L-PMP-ENCLOSED (110X38) - 0831062

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Marker carriers, black, unlabeled, mounting type: adhesive, lettering field size: 110 x 38 mm



### Why buy this product

- The CARRIER/L-PMP-ENCLOSED (110x38) marker carrier has closed housing and is used in conjunction with insertable UC-PMP or PMP-RFID ... labels and PMT and PMST media marking labels
- The CARRIER features snap-in pins which prevent the labels from falling out. In addition, the PMST (10x38) ... labels can be fixed in the carrier using the RVT-PA 3,5 BK fixing rivet
- They are mounted with adhesive tape on the back or using two M5 countersunk screws.
- They are used to clearly identify devices and control cabinets.

### Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	
GTIN	4046356940931

### Technical data

#### Dimensions

Length (b)	110 mm
Width (a)	38 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C
---------------------------------	-------------------

#### General

Color	black
Components	free from silicone and halogen
Flammability rating according to UL 94	V0
Material	PA

## Marker carriers - CARRIER/L-PMP-ENCLOSED (110X38) - 0831062

### Technical data

#### General

RoHS compliant	Yes
Marking mounting type	adhesive

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>