



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Marker carriers - CARRIER-PMP-ENCLOSED (110X38) - 0831068

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Marker carriers, black, unlabeled, mounting type: Screws, rivets, lettering field size: 110 x 38 mm




Why buy this product

- They can be mounted using screws or rivets
- The CARRIER-PMP marker carrier is used in conjunction with insertable UCT-PMP ... labels
- They are used to clearly identify devices and control cabinets
- They can be mounted using screws or screw clamps



Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	 4 046356 941013
GTIN	4046356941013

Technical data

Dimensions

Length (b)	110 mm
Width (a)	38 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C
---------------------------------	-------------------

General

Color	black
Components	free from silicone and halogen
Flammability rating according to UL 94	V0
Material	PA
RoHS compliant	Yes

Marker carriers - CARRIER-PMP-ENCLOSED (110X38) - 0831068

Technical data

General

Marking mounting type	Screws, rivets
-----------------------	----------------

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>