



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Made in America

PATENTED\* MACHINED  
CONTOUR SPRING SUPPORT

UL LISTED

Jewel®

- A. Barrel type banana plug with machined contour spring support\*. Crimped uniformly from 4 sides for maximum strength. Fits industry standard banana jack  $\geq .157"$ . Per ANSI/ESD S1.1 Section 5.4, will maintain greater than 1 pound, less than five pound breakaway force requirement over the life of the cord.
- B. Thermoplastic elastomer strain relief molded on. Flex life average  $>50,000,000$  cycles (per ANSI/ESD S1.1 Bending Life Test, greatly exceeding the 16,000 average cycle requirement). Break load average 30 pounds.
- C. Polyurethane wire insulation. Rapid retraction coil cord compresses length with resulting benefit of less tangling and dragging along work surface. Break load average 30 pounds.
- D. Single T-3161 tinsel conductor. Consisting of 7 strands of polyester wrapped with copper. High flex life. Equivalent is 29 gauge (cir mil and/or ohms).
- E. Autosplice brass crimp secures conductors to resistor lead and provides stress relief for resistor.
- F. One megohm  $\pm 5\%$ , 1/4 watt, series resistor limits current for operator safety. (Per ESD S1.1 section 7.1 current limiting resistance requirement.)
- G. Spring loaded 4mm medical snap socket. Spring separation  $.125" - .165"$ . Provides 1-5 pound breakaway from  $.160"$  snap stud (ANSI/ESD S1.1). Compatible with most major brands.
- H. Jewel® logo molded in compliance with ANSI/ESD S1.1.
- I. Date coded with date of manufacture.
- J. Underwriters Laboratory Listing 90P1C when used with Desco wristbands.
- Jewel® Wrist Bands and Coil Cords meet and exceed the Wrist Band and Wrist Cord requirements of ANSI/ESD S20.20 except that ANSI/ESD S1.1 section 5.9 states "Only wrist straps incorporating a nonstandard [resistor] value shall use the color red on any portion of the wrist strap."

ITEM	DESCRIPTION	Retracted Length		Extended Length	
		X	Y	Nominal	Max
<a href="#">09120</a>	6' Cord, Sapphire	10"	27"	6'	8.5'
<a href="#">09122</a>	6' Cord, Ruby	10"	27"	6'	8.5'
<a href="#">09124</a>	6' Cord, Topaz	10"	27"	6'	8.5'
<a href="#">09126</a>	6' Cord, Emerald	10"	27"	6'	8.5'
<a href="#">09128</a>	6' Cord, Amethyst	10"	27"	6'	8.5'
<a href="#">09121</a>	10' Cord, Sapphire	16"	32"	10'	13'

\*U.S. Patent  
5951337

**Jewel® Lifetime Limited Warranty**

Desco expressly warrants that for a period of 1 year from the date of purchase, Desco Jewel® Wrist Straps and Coil Cords will be free of defects in material (parts) and workmanship (labor). In addition, normal use will not cause Coil Cord resistor strain relief connection or Wrist Band 4 mm snap stud to wear sufficiently to open path-to-ground circuit. Within the lifetime warranty period, a credit for purchase of replacement Desco Jewel® products, or, at Desco's option, the Desco Jewel® product will be repaired or replaced free of charge. If product credit is issued, the amount will be calculated based upon the original invoice purchase price.

See drawing [09105](#) for wristband specifications.

**JEWEL® GROUND CORD, WRIST STRAP, RETRACTILE, COILED**

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: [Desco.com](http://Desco.com)  
PHONE (909) 627-8178 FAX (909) 627-7449  
DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407  
PHONE (781) 821-8370 FAX (781) 575-0172

**DRAWING NUMBER**  
09120

**DATE:**  
November  
2009

**DESCO**