# mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## Fuse - SI FORM C 7,5 A DIN 72581 - 0913702

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Flat-type plug-in fuse, type C, color code: brown, nominal current: 7.5 A

#### Why buy this product

- ${\ensuremath{\,^{\scriptstyle\blacksquare}}}$  With snap-in foot for secure pre-assembly on the PCB
- ${\ensuremath{\,^{\odot}}}$  Fuse holder for flat-type fuses with a maximum nominal voltage of 32 V



#### Key Commercial Data

Packing unit	50 STK
GTIN	4 017918 008666
GTIN	4017918008666

#### Technical data

#### General

Color	brown	
Flammability rating according to UL 94	V0	
Dimensions		
Width	5 mm	
Length	19 mm	
General		
Fuse	С	
Nominal current I <sub>N</sub>	7.5 A	
Nominal voltage $U_N$	24 V	
Standards and Regulations		

Flammability rating according to UL 94	VO
	<u> </u>



## Fuse - SI FORM C 7,5 A DIN 72581 - 0913702

#### Approvals

#### Approvals

Approvals

EAC

Ex Approvals

#### Approval details

EAC

EHC

EAC-Zulassung

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com