



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Fuse - SI FORM C 3 A DIN 72581 - 0913773

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Flat-type plug-in fuse, type C, color code: violet, nominal current: 3 A

The figure shows a version of the article

### Product Features

- ✓ With snap-in foot for secure pre-assembly on the PCB
- ✓ Fuse holder for flat-type fuses with a maximum nominal voltage of 32 V

### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 100193
Weight per Piece (excluding packing)	1.78 GRM
Custom tariff number	85361010
Country of origin	Germany

### Technical data

#### General

Color	violet
Inflammability class according to UL 94	V0

#### Dimensions

Width	5 mm
Length	19 mm
Height NS 35/7,5	13 mm

#### General

Fuse	C
Nominal current $I_N$ (lower level)	3 A

## Fuse - SI FORM C 3 A DIN 72581 - 0913773

### Technical data

#### General

Nominal voltage $U_N$	24 V
-----------------------	------

### Classifications

#### eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27142007
eCl@ss 5.1	27142007
eCl@ss 6.0	27142001
eCl@ss 7.0	27142008
eCl@ss 8.0	27142008

#### ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC002298
ETIM 4.0	EC002298
ETIM 5.0	EC002298

#### UNSPSC

UNSPSC 6.01	30211813
UNSPSC 7.0901	39121410
UNSPSC 11	39121412
UNSPSC 12.01	39121412
UNSPSC 13.2	39121412