



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Wire ————— Tinned copper
 Gauge ————— AWG 28/7 0,089 mm²
 Voltage rating ————— 300 Vr.m.s
 Current rating ————— 1,3 A at 10°C rise above ambient
 Capacity unbalanced ————— 78,7 pF/m nominal at 1MHz
 Impedance unbalanced ————— 75 Ω nominal
 Conductor resistance ————— 225 mΩ/m
 Propagation delay ————— 5,25 ns/m nominal
 Insulation material ————— PVC
 Temperature rating ————— -20°C (operating) | to +105°C
 -30°C (static)
 Insulation resistance ————— 10 000 MΩ/km
 Approvals ————— | UL Listed PLCC-CL2
 | CSA Certified AWM FT-1

- ① : Flat cable, AWG 28/7
- ② : Aluminium / Polyester tape (spiral wrap)
- ③ : 85% minimum coverage tinned copper braid
- ④ : Outer jacket: black PVC

				Dot.	Name	 All Dim. in mm Orig. Size DIN A 4	SEK 18 round flat cable, shielded, 16 poles	Maßstab/ Scale	
				Detail.	12/10/05				JMDR
				Insp.					
				Stand.					
EC01911	25/05/10	SC							
34608	19/09/07	PK							
33239	12/10/05	JMDR							
				Mod.	Dot.	Name	HARTING EURL F-95972 Paris		
09 18 016 7010	100 m (328 feet)						TB 09 18 016 70XX	Blatt/ Page 1 / 2	
09 18 016 7007	30,48 m (100 feet)								
Part number	Length per reel								