

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Accessories

| Identification | Part number | Drawing | Dimensions in mm |
|---|--|--|--|
| Polarization key 1) Part number comprises 2 keys | 09 18 500 99021) | O.75 O.75 O.75 | |
| Locking lever (snaps into place, can be fitted whenever required) | Long: 09 19 000 9903 ²⁾ Short: | Long | Short |
| ²⁾ Order 2 per male header | 09 19 000 99042) | For use with female connector with strain relief clamp | For use with female connector without strain relief clamp |
| Fixing screws for 1.6 mm P.C. board 3) Part number comprises 50 pieces | 09 18 000 99063) | BZ 2.9x6.5 (DIN 7981 or DIN 7049) | For connectors with part numbers 09 18 5xx x9xx: screwing torque 0.2 Nm 09 19 5xx x9xx: screwing torque 0.4 – 0.5 Nm Screw material: Steel (Inox A2) Plating: Nickel |
| Coding system with loss of contact | Code pin 09 18 000 9901 ⁴⁾ | To avoid cross-plugging adjacent conn. A code pin is inserted into the appropri. The corresponding male contact is rem | ate cavity in the female connector. |
| 4) Part number comprises 6 code pins | Removal tool for male contacts 09 99 000 0133 | - Internal | |