

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









This document was generated on 04/14/2017

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0936010263

Status: Active

Overview: GWconnect® Heavy Duty Connectors (HDC)

Description: GWconnect Screw Terminal Insert, Female, 16-Pole, 16A, Numbered 1-16, with Wire

Protection, Silver (Ag) Plated Contacts, Size 16B «77x27»

## **Documents:**

RoHS Certificate of Compliance (PDF)

**Agency Certification** 

CSA 256883 UL E249674

General

Product Family Industrial Connectors / Enclosures

Series <u>93601</u> Component Size 16B «77X27»

Component Type Inserts - Screw Terminal

Insert Series S-I

Overview <u>GWconnect® Heavy Duty Connectors (HDC)</u>

Product Category Heavy Duty Connectors

Product Name GWconnect®

Standard CSA C22.2 NO. 182.3, EN 60664-1, EN 61984, UL

1977

UPC 887191880112

**Physical** 

Durability (mating cycles max) 700
Flammability UL 94V-0
Gender Female
Insert Color Grey
Lock to Mating Part Yes

Material - Contact Copper Alloy
Material - Insert Polycarbonate

Material - Plating
Net Weight
Net Weight
Silver
Number of Rows
Packaging Type
Polarized to Mating Part
Poles
Stripping Length
Silver
Striver
S

Temperature Range - Operating -40°C to +125°C


Tightening Test Torque 0.50 Nm
Wire Size AWG 14-20
Wire Size mm² 0.50-2.50

**Electrical** 

Current - Maximum per Contact 16.0A Voltage - Maximum 500V Wire Protection Yes

**Material Info** 

Engineering Number 7316.6005.0



**EU ELV** 

**Not Reviewed** 

EU RoHS China RoHS

Not Reviewed REACH SVHC Not Reviewed Halogen-Free Status

**Not Reviewed** 

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Not Reviewed ELV Not Reviewed RoHS Phthalates Not Reviewed

**Search Parts in this Series** 

93601 Series

**Mates With** 

93601-0273 Male Screw Terminal Insert

**Use With** 

Size 16B «77x27» Hoods and Housings