

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## HARTING Ethernet cabling - cables and connectors, 4 wire



Ha-VIS EtherRail® stranded cable, Cat. 5e, 4-wire

8 wire

for installation within and outside rail vehicles

4 wire



Cat. 7

Cat. 6<sub>A</sub>

Cable structure
Core structure
Wire insulation
Sheath material

Cable sheath diameter
Transmission performance

Transmission rate

Shielding

PΕ

Operating temperature range

Standard lengths

Colour

Tests / Certificats

Star quad, double shielding

Cat. 5e

4 x AWG 22/7, tinned copper wire, stranded

Cat. 6

PE-Foam Skin, Ø 1.5 mm

Elastomer, electron beam cross-linked

6.6 +/-0.2 mm

Category 5e / Class D up to 100 MHz acc. to ISO/IEC 11 801:2002, EN 50 173-1

10/100 Mbit/s

Shielding foil and shielding braid

-40 °C ... +90 °C

100 m / 500 m / 1000 m

Black

Tests and certificats acc. to DIN, N FF, BS and ASTM,

detail information see Technical Data sheet

Advantages • Robust design

• Fire protection acc. to EN 45 545-1, -2 and -5

 Flame-retardant and heat resistant acc. to DIN 5510 (1-4) and EN 50 264-1

· UV protected

· RoHS compliant

· Halogen free

small Ø permits RJ45 assembly

Identification	Part number Elastomer	Drawing	Dimensions in mm
Ha-VIS EtherRail® stranded cable, Cat. 5e 4-wire  100 m ring 500 m drum 1000 m drum	Black 09 45 600 0108 09 45 600 0118 09 45 600 0128		