## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



NOTES:			THIRD ANGLE PROJ. 🕀 🖯	
I. MATERIALS AND FINISHES:				REV DESCR
SMPM STR PLUG - BeCu, GOLD PLATING				A RELEASE
CABLE - 0.085 SEMI-RIGID CONFORMABLE				B FREQUENCY AND VSWR H
2. ELECTRICAL: A. IMPEDANCE: 50 OHM				
3. PACKAGING: A. QUANTITY: SINGLE PACK B. MARKING: BAG TO BE MARKED "AMPHENOL RF, 95-725-III-XXX AND DATE CODE"				
		——————————————————————————————————————	E TABLE) —	
				·
INTERFACE PER				
MIL-STD-348 SERIES: SMPM PLUG		LENGTH T.	ABLE	
TYP(2)	PART_NUMBER	PART_NUMBER	LENGTH AND TOLERANCE '	L'
	(IMPERIAL)	(METRIC)	IN INCHES [METERS]	
	95-725-111-030	-	3.00 [0.076]	
	-	95-725-111-M010	3.94 [0.100]	
	95-725-111-040	-	4.00 [0.102]	
	95-725-111-050	-	5.00 [0.127]	
	95-725-111-060	-	6.00 [0.152]	
	95-725-111-070	-	7.00 [0.178]	
	95-725-111-080	-	8.00 [0.203]	
	95-725-111-090	-	9.00 [0.229]	
	-	95-725-111-M025	9.84 [0.250]	
	95-725-111-100	-	10.00 [0.254]	
	95-725-111-110	-	11.00 [0.279]	
	95-725-111-120	-	12.00 [0.305]	LENGTH
	95-725-111-180	-	18.00 [0.457]	0" - 23.
	-	95-725-111-M050	19.69 [0.500]	24.00" -
	95-725-111-240	-	24.00 [0.610]	5.0′-2
DESIGN REQUIREMENTS:		95-725-III-M075	29.53 [0.750]	25.0′ &
	95-725-111-360	-	36.00 [0.914]	
X FREQUENCY : DC TO IS GHZ X CONTINUITY		95-725-111-M100	39.37 [1.000]	
X VSWR : 1.30 MAX. [DC-18 GHz] X HI-POT : 500 VRMS	95-725-111-480	- 05 705 111 M000	48.00 [1.219]	
		95-725-111-M200	78.74 [2.000]	
INS. LOSS: dB MAX OTHER				
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES	MATERIAL	DRAWN	DATE	TITLE
±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°	SEE NOTES	ANANDH G	29-Sep-16	SMPM STR PLUG TO
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are		ENGINEER ANANDH G	DATE 29 - Sep - 16	SMPM STR PLUG, USING
confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or			·	SEMI-RIGID CONFORMABL
other data by Amphenol Corp. To to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting	REFERENCE EAR # 7428	APPROVED	DATE	CABLE, VARIOUS LENGTH
rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to	CONFIGURATION LEVEL: In Work	K. CAPOZZI	9-Mar- 8	SCALE: 4.0:1.0 SHEET 2 OF DWG SIZE
or disclosed by said drawings, specifications, or other data.	FINISH	CAD FILE		B
		1		

REVISIONS			1
DESCRIPTION	DATE 20-Mar-17	ECO	APPR
LEASE TO MFG. VSWR REQUIREMENTS UPDATED	19-Mar-18	3344 7383	BMG BMG
VSWR REGORGEMENTS OF DATED	10 Mut 10	1505	
<b>A</b>	SCALE 0.	800	
			-
		-	
			)
			]
TOLERANCE TABLE			
NGTH IN INCHES/FT [METERS]	TOLERANCE		
- 23.90" [0 - 0.607]	±0.25" [0.0	061	
00" - 59.00" [0.610 - 1.499]			
<i>′</i> - 24.9′ [ .524 - 7.6 7]	±2.5%		
0′& UP [7.620 & UP]	±5.0%		
OMER OUTLI		A \A/I	
LL OTHER SHEETS ARE FOR IN			
Am	phenol	RF	
SING 0.085	1		
	.amphenolrf.c		
	.95-725-111	- X X X	
2 OF 2 ITEM NO.95	-725-   -X>	(χ	
KEV	-725-   -X>		
		N /N	