

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## Be Certain with Belden



## **EtherMATE™ Industrial Ethernet Double-Ended Cord Sets**

High-Flex/High Noise, Stranded/Shielded, 24 AWG, PVC Jacket

Туре	0985 656 103	0985 656 104	0985 656 500	0985 656 504
Configuration	M12 to RJ45	M12 (receptacle) to RJ45	RJ45 to RJ45	RJ45 to RJ45 (crossover)
Product Description	Industrial Ethernet double-ended cord set, high-flex, male, M12 to RJ45 straight, 4-pair, 24 AWG, PVC cable, stranded/shielded with teal jacket and orange inserts.	Industrial Ethernet, double-ended cord set, high-flex, M12 female receptacle to RJ45 male, 4-pair, 24 AWG, PVC cable, stranded/shielded, with teal jacket.	Industrial Ethernet double-ended cord set, high-flex, male, RJ45 to RJ45 straight, 4-pair, 24 AWG, PVC cable, stranded/shielded with teal jacket.	Industrial Ethernet double-ended cord set, high-flex, male, RJ45 to RJ45 straight, 4-pair, 24 AWG, PVC cable, stranded/shielded crossover with teal jacket.
Category Rating			CAT5e	
Technical Illustration	46.5 [1.63] — 46.5 [1.63] — 36.3 [1.43] — 36	68000/ETOR PAGEL NUT & PAGEL N	2X 11.7 [487]	
Wiring diagram				
	M12   Color   RJ45	M12   Color   RJ45	RJ45   Color   RJ45	RJ-45S
Face views	5		_	
	,		12345676	
Part number				
	0985 656 103/M	0985 656 104/M	0985 656 500/M	0985 656 504/M
Standard cable lengths				
	0.3 M / 0.5 M / 1 M / 2 M / 3 M / 4 M / 5 M / 10 M / 15 M / 20 M	0.5 M / 1 M / 2 M / 5 M / 10 M / 15 M / 20 M	0.3 M / 0.5 M / 1 M / 2 M / 3 M / 4 M / 5 M / 10 M / 15 M / 20 M / 25 W 30 M / 35 M / 40 M / 45 M / 50 M / 55 M / 60 M / 65 M / 70 M / 75 M / 80 M / 85 M / 90 M	0.6 M / 1 M / 2 M / 5 M / 10 M / 15 M / 30 M



## **EtherMATE™ Industrial Ethernet Double-Ended Cord Sets**

High-Flex/High Noise, Stranded/Shielded, 24 AWG, PVC Jacket

Туре	0985 656 103	0985 656 104	0985 656 500	0985 656 504		
Degree of protection						
Operating temperature range	IP67 / IP20 IP20 IP20 -20°C(-4°F) to +75°C(+167°F)					
Mechanical		-20 0(-41) to	+13 0(+101 1)			
M12						
Molded body	PUR, black					
Coupling nut	Brass, nickel plated					
Contacts	Brass, gold over nickel plated					
Insert	PUR orange					
M12 Receptacle			1			
Housing		Brass, nickel plated				
Insert		PUR, black				
Contacts		Brass, gold plated				
RJ45		<u> </u>				
Housing			copper alloy			
Insert	Clear polycarbonate					
Contacts		50 μ" gold in contact area over nickel plating				
Cable specifications						
Cable jacket		PVC, (sun and				
Color	Teal					
Overall diameter	7.77mm, nominal					
Conductor	24 AWG, 7 strands tinned copper					
Number of pairs	4					
Insulation	Polyethylene 1000'					
Foil shield	Aluminum/polypropylene tape, 100% coverage					
Braided shield	Tinned copper, 65% coverage					
EMI protection	50 dB @ 0.772 MHz - 1000 MHz  ETL rated CMR					
Agency approval Cable type						
Safety Voltage Rating (for cable)	CAT5, high flex / high noise (0985 656 500/504 CAT5e)					
Characteristics						
Olialacteristics						
	NOTE: Vibratio	on & Oil Resistant				
		M12 side only.				
Recommended panel cut out	<b></b>	us c Nus	<del>, N</del>	us		
		Ø15.4 IØ.61"I				
	c The Ut	s cTlus ( + )	. <b></b>	us c <b>?ll</b> us		
		13.6 [.54*]				
		PG-9 PANEL NUT ]				
		PANEL NUT				
		3X 19 [.75*]				
		rked hefore use				

The application of these products in harsh environments should always be checked before use. Specifications subject to alteration.