mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





EtherNet/IP Double-Ended Cord Sets

CAT5e, High-Flex, 2 Twisted Bonded Pair, Stranded/Unshielded, 24 AWG, TPE Jacket

Туре	0985 806 500
Product Description	Ethernet I/P, high-flex, double-ended cord set, RJ45 male to RJ45 male, 24 AWG, teal TPE jacket, stranded/unshielded cable with 2 twisted bonded pairs.
Technical Illustration	22 7 7
	22 11.7 [48]
Wiring diagram	
	Color RJ45 White Orange 1 White Green 3
	Orange 2 Green 6
Face views	
Part number	123 6
	0985 806 500/M
Standard cable lengths	
	0.5 M / 1 M / 2 M / 5 M / 10 M / 15 M / 20 M / 25 M / 30 M / 35 M / 40 M / 45 M / 50 M / 60 M / 70 M / 80 M



EtherNet/IP Double-Ended Cord Sets

CAT5e, High-Flex, 2 Twisted Bonded Pair, Stranded/Unshielded, 24 AWG, TPE Jacket

Туре	0985 806 500
Degree of protection	IP20
Temperature	-20°C to 60°C
Mechanical	
RJ45	
Plug	Polycarbonate
Contacts	Phosphor Bronze, gold plated
Boot	Elastomer Polyolefin
Electrical	
Current rating	1.5A
Voltage rating	30VAC / 42 VDC
Performance	CAT5e, Belden bonded twisted pair cable
Cable specifications	
Cable jacket	TPE
Color	Teal
Overall diameter	.275 "
Conductor	24 AWG stranded tinned copper
Temperature	Operating: -40°C to 75°C / Installation: -25°C to 75°C
Flame test	UL: CMR / CSA: CMG
Continuous Flex	2 million cycles @ 10X,10 million cycles @ 20X bend radius
Characteristics	

The application of these products in harsh environments should always be checked before use. Specifications subject to alteration.