

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## Identification Part No. Drawing M12-male moving load A-coding 21 03 030 1400 **HARTING M12 T-Coupler** 21 03 321 9400 Crimping tool for M12 Crimp 09 99 000 0501 Accessories M12 Crimp D-Sub contacts Tool settings Part number **AWG** 18 Locator 09 67 000 3x76 20 6 5 22 09 99 000 0531 09 67 000 8x76 20, 22, 24 6 09 67 000 5x76 22, 24, 26 6 D-Sub single contacts (500 mating cycles) turned male contacts AWG 22 - 18 / 0.33 - 0.82 mm<sup>2</sup> 09 67 000 3576 09 67 000 8576 AWG 24 - 20 / 0.25 - 0.52 mm<sup>2</sup> 09 67 000 5576 AWG 26 - 22 / 0.13 - 0.33 mm<sup>2</sup> а AWG 22 - 18 1.34 turned female contacts AWG 24 - 20 1.13 09 67 000 3476 AWG 22 - 18 / 0.33 - 0.82 mm<sup>2</sup> AWG 26 - 22 0.88 09 67 000 8476 AWG 24 - 20 / 0.25 - 0.52 mm<sup>2</sup> 09 67 000 5476 AWG 26 - 22 / 0.13 - 0.33 mm<sup>2</sup> M12 dynamometric screwdriver Tightening torque 0.6 Nm for M12-S SW 13 09 99 000 0382 for M12 Slim design SW 15 09 99 000 0646 for M12-L SW 17 09 99 000 0384

03