

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







		PTF Series	
Characteristic	OPTF0075P / OPTF0075PXBL	0PTF00077P	OPTF0078P
use Link	5X20	5X20	5X20
Nounting	PCB	PCB	PCB
ated Current	6.3 Amp.	6.3 Amp.	6.3 Amp.
ated Voltage	250 VAC	250 VAC	250 VAC
ated Power Acceptance	1.6 W	1.6 W	1.6 W
ousing	PA UL-94 V0	PA UL-94 V0	PA UL-94 V0
dmissible Air Temperature	-30° C to 85°C	-30° C to 85°C	-30° C to 85°C
chocksafe Catgory	PC1	PC1	PC1
egree of Protection	IP00	IP00	IP00
ontact Resistance	< 5.0 mΩ	< 5.0 mΩ	< 5.0 mΩ
DE Rated Current	6.3 Amp.	6.3 Amp.	6.3 Amp.
DE Rated Voltage	250 VAC	250 VAC	250 VAC
DE Rated Power Acceptance	1.6 W	1.6 W	1.6 W
R Rated Current	10 Amp.	10 Amp.	10 Amp.
R Rated Voltage	250 VDC	250 VDC	250 VDC
R Rated Power Acceptance	-	-	
	24,4	24.4	24.4
	26 3/0s 15/x22 0.5 x1.2 15 Mounting holes	26 % 5,142 22.6  Mounting holes	22.6 am 0.5 x12 22.6  Mounting holes
	2.20 1.50	0 100 0 100	2.00  1