



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Universal Phantom Manager - Distributed Cat5 KVM Switch

MODEL NUMBER: 0SU52015



Description

The Universal Phantom Manager, the first ever distributed micro-sized KVM switch, is specially designed for single user KVM management of up to 63 servers on a single line making it the ideal solution for high density server and rack environments like server farms, data centers or corporate server rooms.

The micro-sized Specter provides much more power than a conventional switch by freeing up rack space, eliminating cable clutter and maximizing your flexibility.

Advanced Management and Security Options

The Universal Phantom Manager features advanced On Screen Display (OSD) management, including multi-layered security, the most efficient way for monitoring, accessing and controlling your servers.

You can also manage your Phantom system via a serial port, using the Phantom's Control Software or any other third party software.

Less Switch Space Means More Server Space

Phantom's Distributed Switching Technology (DST) divides the KVM switch into smaller subunits: a Manager and multiple Remote units. The Remote units can be placed on the side or back of the rack where they occupy no rack space! Now you can dedicate more of your rack to servers instead of wasting space on switches.

Components

The Universal Phantom Manager system consists of two separate units:

Highlights

- Single user control of up to 63 servers on a single line
- Advanced OSD management and multi-layered security
- Pure hardware solution - BIOS level access
- Scalable - buy only what you need and add as you grow
- Flexible server/KVM console placement up to 110m/360ft away
- No external power supply at Specter units
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

Operating System

- DOS, Windows (3x, 9x, 2000, NT4, ME, XP and later), LINUX, UNIX, HP UX, QNX, SGI, FreeBSD, BeOS, Open VMS, Novell 3.12 - 6, SUN Solaris

Console

- VGA Monitor
- PS/2 Keyboard and Mouse

Resolution

- Supports video resolutions up to 1600 x 1200 @ 75Hz

Package Includes

- 0SU51011
- 3 in 1 KVM Cable Kit



- 1 Universal Phantom Manager (UPM) unit per system
- 1 Remote unit (Phantom Specter II USB or PS/2) per computer up to 63 per line

- RJ11 to DB9 Firmware Upgrade Cable
- Power Cord
- Owner's Manual

Features

- Single user control of up to 63 servers on a single line
- Advanced OSD management and multi-layered security
- Pure hardware solution - BIOS level access
- Scalable - buy only what you need and add as you grow
- Flexible server/KVM console placement up to 110m/360ft away
- No external power supply at Specter units
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
UPC Code	654518201819
Users	1
Console	No
PHYSICAL	
Shipping Dimensions (hwd / in.)	7.000 x 10.000 x 1.000
Shipping Dimensions (hwd / cm)	17.78 x 25.40 x 2.54
Shipping Weight (lbs.)	5.1000
Shipping Weight (kg)	2.31
Unit Dimensions (hwd / in.)	1.6 X 7.1 X 8
Unit Dimensions (hwd / cm)	4.15 X 18 X 20.4
Unit Weight (lbs.)	2.2
Unit Weight (kg)	1.00
Color	White
ENVIRONMENTAL	
Storage Temperature Range	-40 to 40 C (-40 to 104 F)
Operating Temperature	0 to 40 C (32 to 104 F)
COMMUNICATIONS	
Port Control	Hotkeys, OSD



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

IP Remote Access	Yes
CONNECTIONS	
Ports	1
PC/Server Connections	VGA; USB; PS/2
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>