



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!






Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



10 and 20 Position Connectors, with IDC Terminations

10 Positions, Unshielded

20 Positions, Unshielded

Cable Connector Kits

Unshielded cable connector kits are available in 10 and 20 position sizes. They are suitable for field installation using hand tools and for in-plant assembly using either hand or semi-automatic tooling. Both methods allow for unterminated contacts in random positions. The contact design features double IDC slots with crimp insulation support. Additional outer jacket support is provided by a cable clamp applied around the rear of the cover. Two versions are available to suit wire ranges from AWG 30-26 and AWG 26-24.

Tooling

Hand Tool Part No. 734690-1
 MT Matic Bench Terminator
 Part No. 1-876095-8

Cable Connector Mating

Covers are polarized to prevent inverted mating. Keying is not provided to allow flexibility of position in mating to headers. These connectors will not stack end-to-end without loss of one contact column.

Lead Assemblies



AMP can provide lead assemblies to your specification, fully tested and ready for use. A variety of cables can be used.

Row Spacing

Minimum pitch of connector columns is 18mm to allow for operation of the latch.

Materials

Housing – Liquid Crystalline Polymer, Black
Cover – Polybutalene Terephthalate, Black



Wire Size		Insulation Max. Ø mm [inch]	Part Numbers	
AWG	mm'		10 Position	20 Position
Field Installable Kits, single item				
30-26	0.25-0.40	1.0 [.039]	352167-1	352168-1
26-24	0.40-0.50	1.0 [.039]	352167-2	352168-2
Field Installable Kits, 50 items, bulk package				
30-26	0.25-0.40	1.0 [.039]	1-352167-1	1-352168-1
26-24	0.40-0.50	1.0 [.039]	1-352167-2	1-352168-2

Cable Connector Lead Assembly Produced to customer requirements, consult AMP