

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









part number: description:

10-00111

Cable, 2000 mm, 5.5x2.1x7.5mm 50-00010 locking dc plug to same, 18 AWG, UL2468,

30-00007 wire

date: July 30, 2012

rev: A2 page: 1 of 2

Specifications:

| connector description (1) | dc plug, 5.5x2.1xBL7.5xL30 locking style, brass nickel plated, threaded nut 5/16-32, P/N 50-00010 |
|---------------------------|---|
| overmold (2) | 30P, PVC, black |
| wire description (3) | 2C, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, 48P, P/N 30-00007 |
| cable outer diameter | Ø4.4 mm |
| cable color | black |
| cable length | 2000 ± 50 mm |
| twist tie (4) | black |
| current rating | 5 A @ 12 Vdc |


Notes:

Function test: no open, no reversed polarity, no short circuit, no INT

RoHS compliant

Hi-Pot test: 600 Vac, 0.5 mA, 1 second

Mechanical drawing:



tolerance X: ±0.5 mm .X: ±0.3 mm .XX: ±0.05 mm applicable unless otherwise indicated in specification or on drawings Tensility International Corporation reserves the right to substitute parts which are functionally equivalent to the ones specified.

Initial Date



10-00111

Cable, 2000 mm, 5.5x2.1x7.5mm 50-00010 locking dc plug to same, 18 AWG, UL2468,

30-00007 wire

date: July 30, 2012

rev: A2 page: 2 of 2

Revision notes:

| Rev | Date | Description |
|-----|------------------|---|
| Α | May 28, 2009 | initial release |
| A1 | February 6, 2012 | updated connector description |
| A2 | July 30, 2012 | updated to show wire part number 30-00007 |
| | | |
| | | |

Specification Approval

Spec sign-off verifies that you have reviewed the entire specification, tested a sample of the product, and confirm that it meets your requirements. This specification reflects the part as it will be ordered. Orders will not be processed until the specification pages have been initialed and the approval page has been signed. This specification is confidential and is not to be transmitted without prior approval from Tensility.

| Signature | Title ———— |
|-----------|------------|
| Name | Date |
| Company | Branch |