

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









part number: description:

10-00243

Cable, 1830 mm, USB A plug to 5.5x2.1x12 mm 90° 50-00186 plug, center neg, 22 AWG,

UL2468, 30-00008

date: August 23, 2012 rev: A5

rev: A5 page: 1 of 2

Specifications:

connector description (1)	USB-A plug; inner mold: 30P, PVC, black; outer mold: 30P, PVC, black	
connector description (2)	dc plug, 5.5x2.1xL20.5 mm, molding style, spring contacts, for right angle applications, P/N 50-00186	
overmold (3)	30P, PVC, black UL94V0	
wire description (4)	2C, 22 AWG, UL2468, 300V, 80C, 3.6 mm, PVC, 80P, P/N 30-00008	
cable outer diameter	Ø3.6 mm	
cable color	black	
cable length	1830 ± 50 mm	
twist tie (5)	black	
label (6)	tensility.com, Made in China, TENSILITY P/N 10-00243	
current rating	1 A @ 5 Vdc	


Notes:

Function test: no open, no reversed polarity, no short circuit, no INT

RoHS compliant

Hi-Pot test: 600 Vac, 0.5 mA, 1 second

Mechanical drawing:



tolerance X: ±0.5 mm .X: ±0.3 mm .XX: ±0.05 mm applicable unless otherwise indicated in specification or on drawings Tensility International Corporation reserves the right to substitute parts which are functionally equivalent to the ones specified.

Initial Date



10-00243

Cable, 1830 mm, USB A plug to 5.5x2.1x12 mm 90° 50-00186 plug, center neg, 22 AWG,

UL2468, 30-00008

date: August 23, 2012

rev: A5 page: 2 of 2

Revision notes:

Rev	Date	Description
Α	November 10, 2009	initial release
A1	March 17, 2010	added label drawing
A2	September 6, 2011	updated specifications
A3	January 12, 2012	added right angle over-mold dimensions
A4	August 8, 2012	added label specifications, updated to show wire part number 30-00008
A5	August 23, 2012	updated to connector 50-00186

Specification Approval

Spec sign-off verifies that you have reviewed the entire specification, tested a sample of the product, and confirm that it meets your requirements. This specification reflects the part as it will be ordered. Orders will not be processed until the specification pages have been initialed and the approval page has been signed. This specification is confidential and is not to be transmitted without prior approval from Tensility.

Signature	Title ————
Name	Date
Company	Branch