



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us



Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00502	Connector, stereo plug, 3.5xL20.5 mm, brass, gold plated, molding style	2	
2	30-00653	Wire, 2C TS, 28 AWG, 150V, 70C, 2.6 mm, spiral shield, TPU	1	Bio-compatible jacket
3	24-00028	Overmold, TPE, black	2	



Wiring diagram		
50-00502	Wire Color	50-00502
A	White	A
B	Black	B
C	Shield	C

REVISION	DATE	DESCRIPTION	PREPARED:	NOTES	TENSILITY		
A	10/20/2015	Initial release	GL 2016.01.07 14:53:23 -08'00'	RoHS and REACH compliant	20802 Sockeye Place #130 Bend, OR 97701 USA tel 541.323.3228 fax 541.323.4202 800 877.670.7118 www.tensility.com		
A1	11/11/2015	Modified overmold material	VERIFIED: AG 2016.01.08 10:11:10 -08'00'	Function test: no open, no reversed polarity, no short circuit, no INT			
A2	01/07/2016	Modified dimensions	DIMENSIONS ARE IN MILLIMETERS	Functionally equivalent components may be used			
			TOLERANCES: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Drawing in third angle projected			
				DESCRIPTION: Cable, 1830 mm, 3.5 mm 3C 50-00502 slim audio plug to same, 28 AWG, 30-00653, shielded	SIZE A	PART NUMBER 10-02047	
					SCALE: 1:1	WEIGHT:	SHEET 1 OF 1