

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







| ITEM NO. | PART NUMBER | DESCRIPTION | | COMPONENT NOTES |
|----------|-------------|----------------------------------------------------------------------------------------------|---|-----------------|
| 1 | 50-00574 | Connector, USB A 2.0 Plug, molding style, 180°, nickel plated shell, black insulator | 1 | |
| 2 | 50-00576 | Connector, USB A 2.0 receptacle, molding style, 180°, nickel plated shell, black insulator | 1 | |
| 3 | 30-00872 | Wire, 4C, 1PR 28 AWG, 2C 26 AWG, UL2725, 30V, 80C, 4.3 mm, shielded, VW-1, PVC, 79A, USB 2.0 | 1 | |
| 4 | 24-00210 | Overmold, plug, USB A, slim design for aluminum shell | 1 | PVC, black |
| 5 | 24-00217 | Overmold, jack, USB A, slim design for aluminum shell | 1 | PVC, black |
| 6 | 55-00073 | USB A plug aluminum shell, 13x13.5x5.9 mm | 1 | black |
| 7 | 55-00074 | USB A jack aluminum shell, 14.7x7.2x22.5 mm | 1 | black |



| Wiring diagram | | | | | | | |
|----------------|----------------|----------|--|--|--|--|--|
| 50-00574 | Wire Color | 50-00576 | | | | | |
| 1 | Red | 1 | | | | | |
| 2 | White | 2 | | | | | |
| 3 | Green | 3 | | | | | |
| 4 | Black | 4 | | | | | |
| Shell | Drain & Shield | Shell | | | | | |

Notes: Functionally equivalent components may be substituted

| | 1 | | 1 | | 1 | | | | |
|-----------|----------|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-------------------------------------|--------------------------------------|---------|--------------|--|
| Revision: | Date: | Description: | Prepared: | Notes: | | | | | |
| Α | 1/5/2018 | Initial release | AG Digitally signed by AG Date: 2018.01.05 13:32:24-08'00' | RoHS and REACH compliant | ΙТ | TENSILITY | | | |
| | | | Verified: | | tel 1.541.323.3228 800 877.670.7118 | | | | |
| | | | PS Deptably support by PS Deptably support by PS Deptable support by PS Deptable support by San Art Support | intermittent | | fax 1.541.323.4202 web tensility.com | | | |
| | | | | | | - | | • | |
| | | | | Description: Cable, 2000 mm, 50-00574 USB A plug to 50-00576 USB A receptacle, 26/28 AWG, 30-00872 wire | | Size: Part number: | | | |
| | | | | | | 10-02 | 0-02329 | | |
| | | | X.X: ± 0.3 mm X.XX: ± 0.05 mm | | | 1:1 | | Sheet 1 of 1 | |
| | | 5 | 4 | 3 2 | | | | 1 | |