

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







| ITEM NO. | PART NUMBER | DESCRIPTION | QTY. | COMPONENT NOTES |
|----------|-------------|---|------|-----------------|
| 1 | 50-00577 | Connector, USB A 2.0 receptacle, molding style, 180°, nickel plated shell, white insulator | 1 | |
| 2 | 50-00581 | Connector, USB A micro plug, molding style, 180°, nickel plated shell, white insulator | 1 | |
| 3 | 30-00099 | Wire, 4C, 1PR + 2C, 28 AWG, UL2725, 30V, 80C, 3.6mm, shielded, VW-1, PVC, 79A, USB 2.0, white | 1 | |
| 4 | 24-00217 | Overmold, jack, USB A, slim design for aluminum shell | 1 | PVC, white |
| 5 | 24-00218 | Overmold, plug, USB micro and mini, slim design for aluminum shell | 1 | PVC, white |
| 6 | 55-00074 | USB A jack aluminum shell, 14.7x7.2x22.5 mm | 1 | |
| 7 | 55-00075 | USB mini & micro aluminum shell, 9.6x5.8x13 mm | 1 | |



Wiring diagram 50-00577 Wire Color 50-00581 Red 1 White 2 2 3 Green 3 Black 4 & 5 4 Shell Shell Drain & Shield

Functionally equivalent components may be substituted

| Revision: | Date: | Description: | Prepared: | Notes: | | | | |
|-----------|------------|-----------------|---|---|---|------------|--|--------------|
| Α | 01/19/2018 | Initial release | GL Digitally signed by GL Date: 2018.01.19 13:52:23 -08'00' | RoHS and REACH compliant | | TENSII ITY | | |
| | | | Verified: PS Digitally signed by PS Date: 2018.01.19 15:39:10 -08'00' | Function test: no open, no short circuit, no intermittent | tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com | | | |
| | | | Dimensions are in millimeters. Tolerances: X: ± 0.5 mm | Description: Cable, 1000 mm, 50-00577 USB A receptacle to 50- | Size: Part number: A 10-02357 | | | |
| | | | X.X: ± 0.3 mm X.XX: ± 0.05 mm | 00581 USB A micro plug, 28 AWG, 30-00099 wire, white | | 1:1 | | Sheet 1 of 1 |
| | | 5 | 4 | 3 2 | | | | 1 |